	1		2		3	4	5	
				B±0.20 A±0.15 		TECHNICAL CHARACT MATERIAL INSULATOR: NYLON 6 FLAMABILITY RATING: COLOR: WHITE PITCH: 1.25MM ENVIRONMENTAL OPERATING TEMPER/ COMPLIANCE: LEAD F ELECTRICAL INSULATOR RESISTAN	FERISTICS 6 : UL94-V0 ATURE: -40 UP TO 85°C REE AND ROHS NCE: >100 MOHM INDING VOLTAGE: 250V AC/MN 964	
		Pin 1						
R	RoHS Compliant	Pin 1		PROJECTION:	GENERAL TOLERANCE	<u></u>		-
R	RoHS Compliant	Pin 1			GENERAL TOLERANCE .X = ⁺ /_ 0.2 .XX = ⁺ /_ 0.15			
					.X = ⁺ /_ 0.2 .XX = ⁺ /_ 0.15		HOUISING	
R J	10-JUN-15	MIN. TEMP.		1	.X = ⁺ /_ 0.2 .XX = ⁺ /_ 0.15 UNIT: MM	WÜRTH ELEKTRONIK DESCRIPTION: 1.25 MM FEMALE TERMINAL		_
J			AK QL GG		.X = ⁺ /_ 0.2 .XX = ⁺ /_ 0.15		HOUSING SIZE	_

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	oHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE]
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	lD
В]	SCALE:			٢
A	10-SEP-14	PDF	QL	1	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Wurth Elektronik: 653003113322