

Common Mode SCF Coils, SCF Series, Terminal Base Type

Overview



The KEMET SCF coils are common mode chokes with a wide variety of characteristics. These toroidal coils are designed with nanocrystalline metal cores and are useful in various noise countermeasure fields.

Applications

- Audio-visual equipment
- Industrial equipment
- Home appliances
- Power supplies

Benefits

- Nanocrystalline metal core
- Ultra-high inductance
- Ultra-high permeability
- Operating temperature range from -25°C to $+120^{\circ}\text{C}$
- UL 94 V-0 flame retardant rated base and cap



Part Number System

SCF	31B-	200-	2R0	A	020	JH	
Series	Dimension Code (See Dimensions)	Rated Current (A)	Wire Diameter (mm)	Windings	Inductance (mH) Minimum	Terminal Base Type	Internal Control Code
SCF	Blank 12 19 31B 33B 47B 47C	0x = x A xxx = xx.x A Examples: 02 = 2 A 025 = 2.5 A 200 = 20.0 A	Blank R = Decimal point Examples: 0R8 = 0.8 mm 2R0 = 2.0 mm	Blank A = Single C = Triple	xxxx = xx.xx mH xxx = xx.xmH xx = x.x mH Examples: 1100 = 11.00 mH 020 = 2.0 mH 65 = 6.5 mH	J = Vertical type JH = Horizontal type	Blank V

Magnetic Permeability of Ferrite Material


In order to achieve most efficient noise reduction, it is important to select the material according to the target frequency band. Depending on its magnetic permeability, a particular ferrite material or metal material will be effective in a certain frequency band. A schematic representation of the relationship between the magnetic permeability of each material and the corresponding effective band range is shown in Figure 1.

Ferrite materials with higher magnetic permeability are effective in the lower frequency range, while those with lower magnetic permeability are effective in the higher frequency range. Thus, Mn-Zn products are mainly used for reducing conduction noise, while Ni-Zn products are commonly used for radiation noise countermeasures. Metal materials, however, are effective throughout the broadband frequency range, in low as well as high frequencies.

The effective frequency range varies depending on core shape, size, and number of windings. This frequency dependence of the magnetic permeability as shown in the figure serves for reference purposes only. It should be tested on the actual device to determine its effectiveness.

S18H, S15H, 10H, 7H, 5H, 1400L, and 700L are KEMET’s proprietary ferrite material names. Other materials are available upon request.

Figure 1 - Relationship between the magnetic permeability of each material and its effective frequency range



Dimensions – Millimeters

Figure 1




Figure 2




Figure 3





Figure 4



Part Name	Dimensions (mm)				Pin Pitch ¹ (Reference)							Figure
	OD (Maximum)	T (Maximum)	H (Maximum)	L	a	b	c	d	φ	e	R	
SCF-02-130JV	15.0	14.0	15.0	4.5±1.0	5.00	10.00	-	-	-	-	-	Fig. 1
SCF-02-350JH	16.0	15.0	15.5	3.0±0.5	5.08	7.62	-	-	-	-	-	Fig. 2
SCF12-025-1100J	16.0	12.0	16.0	3.1±0.5	6.00	10.00	-	-	-	-	-	Fig. 1
SCF-03-65JV	15.0	14.0	15.0	3.5±1.0	5.00	10.00	-	-	-	-	-	Fig. 1
SCF19-040-0R8A1100J	28.5	23.0	28.5	3.5±1.0	18.00	16.00	-	-	-	-	-	Fig. 3
SCF47B-600-2R2C0005JH	70.0	-	36.5	6.0±3.0	44.00	32.00	-	-	6.0	-	-	Fig. 4
SCF31B-200-2R0A020JH	48.0	42.0	35.0	4.0±1.0	17.00	30.00	-	-	-	-	-	Fig. 5
SCF33B-400-1R6C009JH	50.0	50.0	35.0	5.0±2.0	25.00	30.00	-	-	4.2	-	-	Fig. 6
SCF47B-400-1R8C040J	63.0	39.0	61.0	4.5±1.5	25.00	28.00	-	-	-	-	-	Fig. 7
SCF47C-400-1R8C040JH	70.0	-	38.0	5.0±2.0	44.00	32.00	45°	2.3	-	7.0	1.15	Fig. 8

¹ Pin pitch listed above for reference only. Values not guaranteed.

Dimensions – Millimeters cont.

Figure 5




Figure 6




Figure 7





Figure 8



Part Name	Dimensions (mm)				Pin Pitch ¹ (Reference)							Figure
	OD (Maximum)	T (Maximum)	H (Maximum)	L	a	b	c	d	φ	e	R	
SCF-02-130JV	15.0	14.0	15.0	4.5±1.0	5.00	10.00	-	-	-	-	-	Fig. 1
SCF-02-350JH	16.0	15.0	15.5	3.0±0.5	5.08	7.62	-	-	-	-	-	Fig. 2
SCF12-025-1100J	16.0	12.0	16.0	3.1±0.5	6.00	10.00	-	-	-	-	-	Fig. 1
SCF-03-65JV	15.0	14.0	15.0	3.5±1.0	5.00	10.00	-	-	-	-	-	Fig. 1
SCF19-040-0R8A1100J	28.5	23.0	28.5	3.5±1.0	18.00	16.00	-	-	-	-	-	Fig. 3
SCF47B-600-2R2C0005JH	70.0	-	36.5	6.0±3.0	44.00	32.00	-	-	6.0	-	-	Fig. 4
SCF31B-200-2R0A020JH	48.0	42.0	35.0	4.0±1.0	17.00	30.00	-	-	-	-	-	Fig. 5
SCF33B-400-1R6C009JH	50.0	50.0	35.0	5.0±2.0	25.00	30.00	-	-	4.2	-	-	Fig. 6
SCF47B-400-1R8C040J	63.0	39.0	61.0	4.5±1.5	25.00	28.00	-	-	-	-	-	Fig. 7
SCF47C-400-1R8C040JH	70.0	-	38.0	5.0±2.0	44.00	32.00	45°	2.3	-	7.0	1.15	Fig. 8

¹ Pin pitch listed above for reference only. Values not guaranteed.

Environmental Compliance

All KEMET AC line filters are RoHS Compliant.



Performance Characteristics

Item	Performance Characteristics
Rated Voltage	250 VAC/VDC and 500VAC/VDC
Withstanding Voltage	2,400 VAC (2 seconds, between lines)
Insulation Resistance	> 100 MΩ at 500 VDC (between lines)
Rated Current Range	2 – 60 A
Rated Inductance Range	0.05 – 35 mH minimum
Inductance Measurement Condition	10 kHz, 50 kHz, and 100 kHz
Thermal Class	E (120°C)
Operating Temperature Range	-25°C to +120°C (include self temperature rise)

Table 1 – Ratings & Part Number Reference









Part Number	Rated Voltage AC/DC (V)	Rated Current (A)	Inductance (mH) Minimum	DC Resistance/ Line (mΩ) Maximum	Temperature Rise (K) Maximum	Wire Diameter (mm)	Weight (g) Approximate
SCF-02-130JV	250	2.0	13.00 ¹	115.00	50	0.45	5.0
SCF-02-350JH	250	2.0	35.00 ¹	220.00	45	0.40	5.4
SCF12-025-1100J	250	2.5	11.90 ¹	82.60	70	0.45	5.0
SCF-03-65JV	250	3.0	6.50 ¹	70.00	55	0.50	4.0
SCF19-040-0R8A1100J	250	4.0	11.00 ²	70.00	60	0.80	27.6
SCF47B-600-2R2C0005JH	250	60.0	0.05 ³	0.31	35	2.2 x 3 Parallel	135.0
SCF31B-200-2R0A020JH	500	20.0	2.00 ³	5.20	55	2.00	91.1
SCF33B-400-1R6C009JH	500	40.0	0.90 ³	1.70	65	1.60	105.1
SCF47B-400-1R8C040J	500	40.0	4.00 ¹	2.10	75	1.8 x 3 Parallel	190.0
SCF47C-400-1R8C040JH	500	40.0	4.00 ¹	2.10	55	1.8 x 3 Parallel	192.7

¹ Inductance Measurement Condition: 10 kHz



² Inductance Measurement Condition: 50 kHz

³ Inductance Measurement Condition: 100 kHz

Frequency Characteristics



Frequency Characteristics cont.



Packaging

Type	Packaging Type	Pieces Per Box
SCF-02-130JV	Tray	360
SCF-02-350JH		600
SCF12-025-1100J		1,080
SCF-03-65JV		360
SCF19-040-0R8A1100J		240
SCF47B-600-2R2C0005JH		36
SCF31B-200-2R0A020JH		80
SCF33B-400-1R6C009JH		36
SCF47B-400-1R8C040J		
SCF47C-400-1R8C040JH		

Handling Precautions

Precautions for product storage

AC Line Filters should be stored in normal working environments. While the chokes themselves are quite robust in other environments, solderability will be degraded by exposure to high temperatures, high humidity, corrosive atmospheres, and long term storage.

KEMET recommends that maximum storage temperature not exceed 40°C and maximum storage humidity not exceed 70% relative humidity. Atmospheres should be free of chlorine and sulfur bearing compounds. Temperature fluctuations should be minimized to avoid condensation on the parts. Avoid storage near strong magnetic fields, as this might magnetize the product.

For optimized solderability, AC line filters stock should be used promptly and preferably within 6 months of receipt.

Product temperature rise values

The values listed for temperature rise are the result of self-heating in wires when the rated current (commercial frequency) is applied.

When using the product, check and evaluate the value of the core temperature rise under actual operating conditions.

KEMET Electronics Corporation Sales Offices

For a complete list of our global sales offices, please visit www.kemet.com/sales.

Disclaimer

All product specifications, statements, information and data (collectively, the "Information") in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Statements of suitability for certain applications are based on KEMET Electronics Corporation's ("KEMET") knowledge of typical operating conditions for such applications, but are not intended to constitute – and KEMET specifically disclaims – any warranty concerning suitability for a specific customer application or use. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by KEMET with reference to the use of KEMET's products is given gratis, and KEMET assumes no obligation or liability for the advice given or results obtained.

Although KEMET designs and manufactures its products to the most stringent quality and safety standards, given the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required.

When providing KEMET products and technologies contained herein to other countries, the customer must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the International Traffic in Arms Regulations (ITAR), the US Export Administration Regulations (EAR) and the Japan Foreign Exchange and Foreign Trade Act.

KEMET is a registered trademark of KEMET Electronics Corporation.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

KEMET:

[SCF-02-350JH](#) [SCF-03-65JV](#) [SCF-02-130JV](#) [SCF19-040-0R8A1100J](#) [SCF33B-400-1R6C009JH](#) [SCF47C-400-1R8C040JH](#) [SCF47B-400-1R8C040J](#) [SCF12-025-1100J](#) [SCF31B-200-2R0A020JH](#) [SCF47B-600-2R2C0005JH](#)