# 🖌 gembird®

## 3DP-PLA-FL-01-BK Filament, PLA Flexible, Black, 1.75 mm, 1 kg

### **VERSATILE & EASY TO USE**

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowbility, no need to post-treatment



#### Features

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers

#### Specifications

Material: PLA, 1.75 mm diameter Weight: 1 kg/spool (2.2 lbs) Length: approx. 340 m Density at 21.5 °C: 1.237 g/cm3 Melt Flow Index at 10min, 2.16kg: 6.38 Melt Point: 195 220 °C Heat-Deflection-Temperature at 0.455 MPa: 137 °C Yield Strength at 5mm/min: > 8.9 MPa Tensile Break: 580 ... 600 % Diameter: 1.75 ± 0.05 mm

#### Packaging

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 8 0.035 12.16 208x208x83 mm 350x430x230 mm CN 8716309124003 3916909000

#### System requirements

A 3D printer with 1.75 mm extruder of temperature around 200  $^\circ,$  suitable for PLA filament

#### Certificates



Copyright © 2009–2023, Gembird Software Ltd.

Gembird Europe B.V. Wittevrouwen 56, 1358CD Almere, The Netherlands. Phone: +31-36-5211588