Note: This datasheet may be out of date

Please download the latest datasheet of NFZ2MSD301SZ10# from the official website of Murata Manufacturing
Co. Ltd.

https://www.murata.com/en-global/products/productdetail?partno=NFZ2MSD301SZ10%23

NFZ2MSD301SZ10#

"#" indicates a package specification code.










< List of part numbers with package codes > NFZ2MSD301SZ10L



Appearance & Shape







- 1. NFZ2MSD_SZ is a noise filter designed for noise suppression of audio lines in car navigation systems, car radios, and other automotive information equipment.
- Can be used in high current circuits due to its low DC resistance.
- 3. Low magnetic flux leakage with magnetically shielded structure.
- 4. Meets 125°C maximum operating temperature.

Applications

Automotive Usage	Infotainment
---------------------	--------------



Packaging Information

Packaging	Specifications	Minimum Order Quantity
L	180mm Embossed Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/07/18



$\underline{Co., Ltd.} \\ https://www.murata.com/en-global/products/productdetail?partno=NFZ2MSD301SZ10\%23$

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ NFZ2MSD301SZ10\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

NFZ2MSD301SZ10#

"#" indicates a package specification code.

Note: This datasheet may be out of date



Shape	SMD
Size Code (in mm)	2016
Size Code (in inch)	0806
Length	2.0mm
Length Tolerance	±0.2mm
Width	1.6mm
Width Tolerance	±0.2mm
Thickness	1.2mm
Thickness Tolerance	max.
Rated Current	3.8A
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.0188g
Number of Circuit	1
DC Resistance(max.)	26mΩ
DC Resistance	26mΩ max.
Impedance (at 10MHz)	21Ω
Impedance (at 10MHz) Tolerance	±30%

Impedance (at 100MHz)	300Ω
Impedance (at 100MHz) Tolerance	(Тур.)
Operating Temperature Range (Self- temperature rise is included)	-40°C to 125°C

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/07/18


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

https://www.murata.com/en-global/products/productdetail?partno=NFZ2MSD301SZ10%23


NFZ2MSD301SZ10#

"#" indicates a package specification code.






Max. current (DC, AC) as function of product temperature (derating curve).



Impedance-Frequency Characteristics



Derating of Rated Current

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/