# **CUI** DEVICES

#### MODEL: PJ-008A | DESCRIPTION: DC POWER JACK

#### **FEATURES**

- 2.0 mm center pin
- 2.5 A rating
- right angle orientation
- panel mount



.....



#### **SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated input voltage			24		Vdc
rated input current				2.5	А
contact resistance <sup>1</sup>	between terminal and mating plug between terminal in a closed circuit			50 30	mΩ mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	at 50/60Hz for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life			5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				

Note:

.....


When measured at a current of less than 100 mA/1 kHz.
All specifications measured at 10~35°C, humidity at 45~85%, under standard atmospheric pressure, unless otherwise noted.

#### **SOLDERABILITY**


parameter	conditions/description	min	typ	max	units
hand soldering	for 3~4 seconds	340	350	360	°C


#### **MECHANICAL DRAWING**

units: mm tolerance: X.X ±0.2 mm X.XX ±0.1 mm X.XXX ±0.05 mm




	MATERIAL	PLATING
center pin	copper	nickel
terminal 1	brass	tin
terminal 2	copper alloy	tin
terminal 3	brass	tin
insulators	PBT	
plastic	PBT	







.....



12.2



-15.5



MATING PLUG	
Jack Insertion Depth: 9.0	mm

SCHEMATIC	
Model	PJ-008A
Center Pin	Ø2.0 mm

.....

#### **REVISION HISTORY**

rev.	description	date
1.0	initial release	04/17/2006
1.01	increased voltage rating	04/28/2016
1.02	brand update	10/29/2019
1.03	updated housing mold	07/01/2020

The revision history provided is for informational purposes only and is believed to be accurate.

## **CUI** DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

.....

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Devices: PJ-008A