

swissbit®

Product Fact Sheet

# Industrial CompactFlash™ Card

## C-500 Series

up to UDMA6 / MDMA4 / PIO6, SLC

Commercial and Industrial  
Temperature Grade

Date: April 1, 2020  
Revision: 1.01



## Product Summary

- **Capacities:** 128 MBytes, 256 MBytes, 512 MBytes, 1 GByte, 2 GBytes, 4 GBytes, 8 GBytes, 16 GBytes, 32 GBytes, 64 GBytes
- **Form Factor:** CompactFlash Type I Card (36.4mm x 42.8mm x 3.3mm)
- **Compliance:** CFA 5.0 (CFA 6.1 compatible)  
PCMCIA spec. 2.1 & PC Card ATA Interface spec. 8, 7, 6, and 5,  
ATA-7 standard compatible in True IDE mode, up to UDMA6 / MDMA4 / PIO6 support
- **Performance:**
  - Read Performance: Sequential Read up to 64 MBytes/s, Random Read IOPS up to 3,200
  - Write Performance: Sequential Write up to 44 MBytes/s, Random Write IOPS up to 1,900
- **Operating Temperature Range<sup>1</sup>:**
  - Commercial: 0 °C to 70°C
  - Industrial: -40 °C to 85°C
- **Storage Temperature Range:**
  - -50 °C to 100 °C
- **Operating Voltage:** 3.3V ± 10% / 5V ± 10%
- **Data Retention:** 10 Years at Life Begin (JESD47), 1 Year at Life End
- **Shock/Vibration:** 1,500 *g* / 20 *g*
- **Mean Time Between Failure:** > 3,000,000 hours
- **Data reliability:** < 1 non-recoverable error per 10<sup>17</sup> bits read
- **Electromagnetic Compatibility Tests:** Radiated Emission; Radiated Immunity; Electrostatic Discharge

## Product Features

- SLC Flash with 100,000 Program/Erase Cycles and Reduced Write Amplification
- Global, Dynamic and Static Wear Leveling to maximize system write endurance
- Page Mode Flash Translation Layer (FTL) for best in class write performance and endurance
- Data Care Management
  - Read Disturb Management and Dynamic Data Refresh for maximized retention
  - Passive: Background Media Scan
- Lifetime Enhancements
  - Dynamic Bad Block Remapping
  - Write Amplification Reduction
  - Intelligent Garbage Collection
- Management of unexpected power loss
- Up to UDMA6, MDMA4, PIO6 interface speed (max 133 MB/s burst)
- Security Feature Set Support
- Optimized for fast boot-up times
- In-Field Firmware Update without user data loss
- Detailed Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)
- Life Cycle Management
- Controlled "Locked" BOM
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

### Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addresses the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

<sup>1</sup> Adequate airflow is required to ensure the drive temperature, as reported in the S.M.A.R.T. data, does not exceed the specified maximum operating temperature.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Swissbit:

[SFCF008GH1AF2TO-C-MS-527-STD](#) [SFCF008GH1AF2TO-I-MS-527-STD](#) [SFCF2048H1AF2TO-C-DS-527-STD](#)  
[SFCF4096H1AF2TO-C-QT-527-STD](#) [SFCF4096H1AF2TO-I-QT-527-STD](#) [SFCF016GH1AF4TO-C-MS-527-STD](#)  
[SFCF032GH1AF2TO-C-QT-527-STD](#) [SFCF0512H1AF1TO-C-MS-527-STD](#) [SFCF064GH1AF4TO-C-QT-527-STD](#)  
[SFCF1024H1AF2TO-C-MS-527-STD](#) [SFCF016GH1AF4TO-I-MS-527-STD](#) [SFCF032GH1AF2TO-I-QT-527-STD](#)  
[SFCF0512H1AF1TO-I-MS-527-STD](#) [SFCF064GH1AF4TO-I-QT-527-STD](#) [SFCF1024H1AF2TO-I-MS-527-STD](#)  
[SFCF2048H1AF2TO-I-DS-527-STD](#) [SFCF0128H1AF1TO-C-MS-527-STD](#) [SFCF0128H1AF1TO-I-MS-527-STD](#)  
[SFCF0256H1AF1TO-C-MS-527-STD](#) [SFCF0256H1AF1TO-I-MS-527-STD](#) [SFCF008GH1AF2TO-I-MS-523-STD](#)  
[SFCF016GH1AF4TO-I-MS-523-STD](#) [SFCF0256H1AF1TO-I-MS-523-STD](#) [SFCF1024H1AF2TO-I-MS-523-STD](#)  
[SFCF2048H1AF2TO-C-DS-523-STD](#) [SFCF2048H1AF2TO-I-DS-523-STD](#) [SFCF4096H1AF2TO-I-QT-523-STD](#)