



CLD-9024-T2-E25

24V / 3.75A Desktop type AC/DC adaptor



■ Features:

- Universal AC input / Full range
- Desktop type, Isolation class II design
- ErP step II / CEC level VI compliance
- No load power consumption $P < 0.075W$
- Protections: Overload / Short circuit / Over Temperature

ELECTRICAL SPECIFICATION



MODEL	CLD-9024-T2-E25
OUTPUT	
Rated Voltage	24V
Rated Current	3.75A
Current Range	0 ÷ 3.75A
Rated Power	90W
Line Regulation	± 2%
Load Regulation	± 5%
Tolerance [3]	± 5%
Ripple & Noise (max.) [2]	480mV _{p-p}
Setup, Rise Time [4]	4s, 20ms / 230VAC at full load
Hold up Time (typ.)	50ms / 230VAC at full load

INPUT	
Voltage Range	90 ÷ 264VAC
Frequency Range	47 ÷ 63Hz
Efficiency (typ.)	84,12%
AC Current (typ.)	2A / 115VAC, 0.6A / 230VAC
No load Power Consumption (max.)	0.075W

PROTECTIONS	
Overload	Range: 120 ÷ 150% Type: hiccup mode, auto-recovery.
Short Circuit	Type: hiccup mode, auto-recovery.
Over voltage	Range: 28 ÷ 32V, auto-recovery. Type: hiccup mode, auto-recovery



CLD-9024-T2-E25

24V / 3.75A Desktop type AC/DC adaptor

WORKING ENVIRONMENT

Working Temperature	0°C ÷ 40°C
Working Humidity	5 ÷ 95% RH non-condensing
Storage Temperature and Humidity	-20°C ÷ 85°C, 5 ÷ 95% RH non-condensing

SAFETY and EMC REGULATIONS

Safety Standards	Compliance to EN 60950-1
Withstand Voltage	I-P/O-P: 5.3kVAC
Isolation Resistance	IN/OUT: 100MΩ/500VDC/25°C/70%
EMC Emission	Compliance to EN55032
EMC Immunity	Compliance to EN61000-4-2, -3, -4, -5
Harmonic Current	Compliance to EN61000-3-3; EN61000-3-2

OTHERS

Wire and plug	Wire: 20AWG, length = 100cm ±50mm	Plug: 2.1/5.5, positive inside
Dimensions	170 x 65 x 40mm (L x W x H)	
Net Weight	386g	

1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF i 47μF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

