# KEMET Part Number: C20ALGR6100AASK

C20A, Film, Metallized Polypropylene, AC Filter, 100 uF, 10%, 640 VAC, 1400 VDC




| General Information | |
|---|---|
| **Supplier:** | KEMET |
| **Series:** | C20A |
| **Dielectric:** | Metallized Polypropylene |
| **Style:** | Can |
| **Features:** | Single Phase PFC |
| **RoHS:** | Yes |
| **Lead:** | Threaded Studs M10 |
| **Miscellaneous:** | Thermal Resistance = 4.4 C/W |

| Dimensions | |
|---|---|
| **D** | 95mm +/-0.5mm |
| **L** | 247mm +/-2mm |
| **W** | 21mm +/-1mm |
| **S** | 35mm +/-1mm |

| Packaging Specifications | |
|---|---|
| **Mounting:** | Bolt - M12x16 |
| **Packaging:** | Bulk, Bag |

| Specifications | |
|---|---|
| **Capacitance:** | 100 uF |
| **Capacitance Tolerance:** | 10% |
| **Voltage AC:** | 640 VAC |
| **Voltage DC:** | 1400 VDC |
| **Temperature Range:** | -25/+70C |
| **Rated Temperature:** | 70°C |
| **Insulation Resistance:** | 10 MOhms |
| **Max dV/dt:** | 30 V/us |
| **Resistance:** | 1.3 mOhms (10kHz) |
| **Ripple Current:** | 60 Amps (10kHz 40C) |
| **Inductance:** | 170 nH |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2019 KEMET