MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia
VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com
www.mikroe.com

UVC Click

PID: MIKROE-4144

UVC Click is ultraviolet sensing board based on GUVC-T21GH ultraviolet sensor from GenUV, capable of measuring UVC spectrum in range of 220nm up to 280nm and light intensity from 0mW/cm² up to 9.3mW/cm². With high sensitivity and good solar blindness it can be a perfect solution for monitoring sterilization lamps used in ultraviolet germicidal irradiation (UVGI), a desinfection metod that is becoming essential tool in battle against viruses and bacteria.

UVC Click board™ is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board™ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS™ socket.

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia
VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com
www.mikroe.com

Specifications

Type	UVC Light,Optical
Applications	It can be used for UV measurement applications, sterilization lamp monitoring, prototyping of wearables, handsets, and various consumer electronics based on received UV light
On-board modules	GUVC-T21GH
Key Features	UVC sensing with 12-bit resolution, High Sensitivity, Good Solar Blindness
Interface	Analog,I2C
Compatibility	mikroBUS
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V or 5V

Resources

mikroBUS™ Standard specification

LibStock: mikroSDK

Click board catalog

Downloads

UVC click schematic

UVC click example on Libstock

GUVC-T21GH datasheet

UVC click 2D and 3D files

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mikroe](#):
  [MIKROE-4144](#)