

Automotive and Industrial Grade SMD Crystal Oscillator



ASDAIG



2.50 x 2.00 x 0.95mm
 RoHS/RoHS II Compliant
 MSL = N/A: Not Applicable


Features

- AEC-Q200 Qualified
- Automotive Grade 1: -40°C to +125°C
- TS16949 Production Line Certified
- PPAP Available Upon Request
- Hermetically Seam-sealed Ceramic Package
- RoHS/RoHS II Compliant and Pb free

Applications

- Infotainment Systems
- Keyless Entry & Startup
- GPS & Navigation
- Comfort control
- ADAS (Advanced Driver Assistance Systems)
- Vehicle to Vehicle Communication
- LiDAR (Light Detection and Ranging)
- In-vehicle Networking
- Powertrain & Drive Control
- Power Control & Conversion
- Industrial Control & Automation

Part Identification (left blank if standard)



Automotive and Industrial Grade SMD Crystal Oscillator



ASDAIG



2.50 x 2.00 x 0.95mm
RoHS/RoHS II Compliant
MSL = N/A: Not Applicable

Electrical Specifications

Parameters		Min.	Typ.	Max.	Unit	Notes	
Frequency Range		1.25		156.25	MHz		
Operating Temperature Range		-40		+125	°C	Option "blank"; See options	
Storage Temperature		-55		+125	°C	Option "X, blank, L, N"	
Overall Frequency Stability [Note 1]		-50		+50	ppm	Option "C"; See options	
		-100		+100		Option "blank"; See options	
		-150		+150		Option "R"; See options	
Supply Voltage (V_{dd})		+1.71	+1.8 ~ +3.3	+3.465	V	Option "5"	
		+3.135	+3.3	+3.465		Option "blank"	
		+2.85	+3.0	+3.15		Option "1"	
		+2.375	+2.5	+2.625		Option "2"	
		+1.71	+1.8	+1.89		Option "3"	
Supply Current (I_{dd}) into 15pF Load		$V_{dd} = 3.3$ V		4.0	7.0	mA	1.250~39.999 MHz
				9.0	13.0		40.000~48.999 MHz
				15.0	20.0		49.000~156.000 MHz
		$V_{dd} = 3.0$ V		3.5	6.0		1.250~39.999 MHz
				8.0	12.0		40.000~48.999 MHz
				15.0	20.0		49.000~156.000 MHz
		$V_{dd} = 2.5$ V		3.0	5.0		1.250~39.999 MHz
				7.0	10.0		40.000~48.999 MHz
				15.0	20.0		49.000~156.000 MHz
		$V_{dd} = 1.8$ V		2.0	4.0		1.250~39.999 MHz
				4.0	7.0		40.000~48.999 MHz
				10.0	15.0		49.000~156.000 MHz
Disable Current				10.0	μA		
Output Load				15	pF	CMOS	
Output Voltage		V_{OH}	$0.9 * V_{dd}$		V		
		V_{OL}		$0.1 * V_{dd}$			
Tri-state function		"1" ($V_{IH} \geq 0.7 * V_{dd}$) or Open: Oscillation; "0" ($V_{IH} < 0.3 * V_{dd}$): No oscillation/Hi Z					
Aging		-2.0		+2.0	ppm	@25°C ± 3°C First year	
Symmetry @1/2 V_{dd}		40	50	60	%	Option "blank"	
		45	50	55		Option "S"	
Start-up Time			2.0	5.0	ms		
Rise/Fall Time (T_r/T_f)		$V_{dd} = 3.3$ V		2.5	6	ns	1.250~39.999 MHz
				2	4		40.000~156.000 MHz
		$V_{dd} = 3.0$ V		2.5	6	ns	1.250~39.999 MHz
				2	4		40.000~156.000 MHz
		$V_{dd} = 2.5$ V		3	7	ns	1.250~39.999 MHz
				2.5	5		40.000~156.000 MHz
		$V_{dd} = 1.8$ V		3.5	8	ns	1.250~39.999 MHz
				3	6		40.000~156.000 MHz

Note 1: Inclusive of initial tolerance at time of shipment, changes in supply voltage, load, temperature and 1st year



ASDAIG





2.50 x 2.00 x 0.95mm
 RoHS/RoHS II Compliant
 MSL = N/A: Not Applicable



Electrical Specifications Cont.

Parameters		Min.	Typ.	Max.	Unit	Notes
RMS Phase Jitter @ +25°C (10-39MHz: 12kHz to 5MHz) (>39MHz: 12kHz to 20MHz)	$V_{dd} = 3.3\text{ V}$		0.5	< 1.0	ps	
	$V_{dd} = 3.0\text{ V}$		0.5	< 1.0		
	$V_{dd} = 2.5\text{ V}$		0.5	< 1.0		
	$V_{dd} = 1.8\text{ V}$		0.5	< 1.0		
Period Jitter RMS	$V_{dd} = 3.3\text{ V}$		3.0	5.0	ps	
	$V_{dd} = 3.0\text{ V}$		3.0	5.0		
	$V_{dd} = 2.5\text{ V}$		3.0	5.0		
	$V_{dd} = 1.8\text{ V}$		3.0	5.0		

Mechanical Dimensions



Recommended Land Pattern



Pin #	Function
1	Tri-state
2	GND/Case
3	Output
4	V_{dd}

Note: Recommend using an approximately 0.01uF bypass capacitor between PIN 2 and PIN 4

Dimensions: mm




ASDAIG



2.50 x 2.00 x 0.95mm
 RoHS/RoHS II Compliant
 MSL = N/A: Not Applicable

Reflow Profile



Zone	Description	Temperature	Time
1	Preheat / Soak	$T_{SMIN} \sim T_{SMAX}$ 150°C ~ 180°C	60 ~ 120 sec.
2	Reflow	T_L 230°C	30 ~ 40 sec.
3	Peak heat	T_P 260°C ± 5°C	5 sec. MAX

Automotive and Industrial Grade SMD Crystal Oscillator




ASDAIG



2.50 x 2.00 x 0.95mm
RoHS/RoHS II Compliant
MSL = N/A: Not Applicable

Packaging

Tape and Reel:
T: 1,000pcs/reel
T3: 3,000pcs/reel



Dimensions: mm

ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 09.09.2019

ABRACON IS
ISO9001-2015
CERTIFIED

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

[ASDAIG2-27.000MHz-X-C-T](#) [ASDAIG2-27.000MHz-X-K-T](#) [ASDAIG2-48.000MHz-X-C-T](#) [ASDAIG-26.000MHz-X-K-T](#)
[ASDAIG3-26.000MHz-C-T](#) [ASDAIG3-26.000MHz-X-K-T](#) [ASDAIG3-27.000MHz-X-K-T](#) [ASDAIG-33.000MHz-X-K-T](#)
[ASDAIG3-33.000MHz-C-T](#) [ASDAIG3-33.000MHz-X-K-T](#) [ASDAIG-48.000MHz-X-K-T](#) [ASDAIG-32.000MHZ-C-S-T](#)
[ASDAIG-32.000MHZ-X-K-S-T](#) [ASDAIG-27.000MHZ-C-S-T](#) [ASDAIG3-27.000MHZ-X-K-S-T](#) [ASDAIG3-16.000MHZ-C-S-](#)
[T](#) [ASDAIG3-16.000MHZ-X-K-S-T](#) [ASDAIG-16.000MHZ-C-S-T](#) [ASDAIG-24.000MHZ-C-S-T](#) [ASDAIG-16.000MHZ-X-K-](#)
[S-T](#) [ASDAIG-24.000MHZ-X-K-S-T](#)