



VS-211H2

2x1 Automatic 4K UHD HDMI Standby Switcher



The VS-211H2 is a high-performance automatic switcher for 4K UHD HDMI video signals. Offering priority and last-connected switching options, it automatically switches according to the selected switching scheme based on active video signal detection. It supports resolutions up to 4K@60Hz (4:4:4) UHD.

FEATURES

- Max. Data Rate - 17.82Gbps (5.94Gbps per data channel).
- Resolution Support - Up to 4K@60Hz (4:4:4) UHD.
- Kramer Equalization and re-Klocking Technology.
- HDTV Compatible.
- HDMI & HDCP 2.2 Compliant.
- 3D Pass-Through.

TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors.
OUTPUTS:	1 HDMI connector.
MAX. DATA RATE:	17.82GBPS (5.94Gbps per graphic channel).
MAX. RESOLUTION4K@60 UHD (4: 4:4).	4:4).
COMPLIANCE WITH HDMI STANDARD:	HDCP and HDMI.
CONTROLS:	Status/priority DIP–switches, contact closure remote control.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	–40° to +70°C (–40° to 158°F).
HUMIDITY:	10% to 90%, RHL non–condensing.
POWER CONSUMPTION:	5V DC, 400mA.
DIMENSIONS:	12cm x 7.15cm x 2.44cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.156kg (0.34lbs) approx.
SHIPPING DIMENSIONS:	23.2cm x 12cm x 8.9cm (9.1" x 4.7" x 3.9") W, D, H.
SHIPPING WEIGHT:	0.625kg (1.38lbs) approx.
INCLUDED ACCESSORIES:	Power supply 5.2V DC/4A desktop.
OPTIONS:	RK–3T 19" rack adapter.

