

This document was generated on 08/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0039012026		
Status:	Active		
Overview:	Mini-Fit Family Power Con		
Description:		Dual Row, 2 Circuits, UL 94V-0, with Panel Mounting Ears,	3/2
	Natural		
Documents:			
<u>3D Model</u>		Application Specification 55560001-AS-000 (PDF)	
<u>3D Model (PDF)</u>		Application Specification AS-5557-001-001 (PDF)	
Drawing (PDF)		Packaging Specification PK-5559-001-001 (PDF)	
Product Specificati	on PS-45750-001-001 (PDF)	Test Summary 55560010-TS-000 (PDF)	Series image - Reference only
Product Specification PS-5556-001-001 (PDF) RoHS Certificate of Compliance (PDF)			
, 			EUELV
Agency Certificat	ion		Not Relevant
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
			Compliant
General			REACH SVHC
Product Family		Crimp Housings	Not Contained Per -
Series		<u>5559</u>	D(2021)4569-DC (8
Application		Power, Wire-to-Board, Wire-to-Wire	July 2021)
Comments		Current = 13A max. per circuit when header is mated	Halogen-Free
		to a receptacle loaded with <u>45750</u> series terminals	<u>Status</u>
		crimped to 16 AWG wire See Molex product	Low-Halogen
		specification PS-45750-001 for additional current	For more information, please visit Contact US
		derating information.	
Overview		Mini-Fit Family Power Connectors	China ROHS Green Image
Product Name		Mini-Fit Jr.	ELV Not Relevant
UPC		800753584280	RoHS Phthalates Not Contained
Physical			
Breakaway		No	
Circuits (maximum)	2	Search Parts in this Series
Color - Resin		z Natural	<u>5559</u> Series
Flammability		94V-0	
Gender		Plug	Mates With
Glow-Wire Capable	9	No	Mini-Fit Jr. Receptacle Housing <u>5557</u>
Material - Resin		Nylon	<pre></pre>
Net Weight		1.280/g	<pre>classic recently</pre>
Number of Rows		2	
Packaging Type		Bag	Use With
Panel Mount		Yes	
Pitch - Mating Inter	face	4.20mm	Mini-Fit Male Crimp Terminals <u>5558</u> br>Mini-Fit Plus HCS Crimp Terminals
Pitch - Termination		4.20mm	46012 dr>Mini-Fit Jr. Grounding Pin 30490
Polarized to Mating		Yes	<u>40012</u>
Stackable	g	No	, 797580013
Temperature Rang	e - Operating	-40° to +105°C	, <u>131300013</u>
	,		
Electrical			
Current - Maximun	n per Contact	13.0A	
Matarial Info			
Material Info			
Engineering Numb		5559-02P-210	
Reference - Drawing Numbers			
Application Specifi	-	55560001-AS-000, AS-5557-001-001	
Packaging Specification		PK-5559-001-001	
Product Specification		PS-45750-001-001, PS-5556-001-001	

This document was generated on 08/13/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION