

Part Number: 395443004

Product Description: 5.08mm Pitch Eurostyle Vertical Fixed Mount PCB Terminal Block, 4

Circuits

Series Number: 39544

Status: Active

Product Category: Terminal Blocks and

Barrier Strip



Documents & Resources

Drawings

Drawing 395443004_sd.pdf

3D Models and Design Files3D Model 395443004_stp.zip

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

| Status | Active |
|----------------|--|
| Category | Terminal Blocks and Barrier Strip |
| Series | 39544 |
| Description | 5.08mm Pitch Eurostyle Vertical Fixed Mount PCB Terminal Block, 4 Circuits |
| Application | N/A |
| Component Type | One Piece |
| Product Family | Eurostyle Terminal Blocks |
| Product Name | Eurostyle Fixed Mount |
| Туре | Euro Block |
| UPC | 822350547017 |

Agency

| UI | F48521 |
|-----|---------|
| O E | 1 10321 |

Electrical

| Current - Maximum per Contact | 15.0A |
|-------------------------------|-------|
| Voltage - Maximum | 300V |

Physical

| Circuits (Loaded) | 4 |
|-----------------------------|------------|
| Entry Angle | Horizontal |
| Lock to Mating Part | None |
| Net Weight | 5.650/g |
| Number of Rows | 1 |
| Orientation | Vertical |
| Panel Mount | No |
| PC Tail Length | 3.00mm |
| PCB Thickness - Recommended | 2.00mm |

| Pitch - Mating Interface | 5.08mm |
|-------------------------------|------------------------|
| Pitch - Termination Interface | 5.08mm |
| Polarized to Mating Part | N/A |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |
| Wire Size (AWG) | 12, 14, 16, 18, 20, 22 |
| Wire Size mm ² | 0.33-3.31 |

Solder Process Data

| Max-Duration | 5 |
|------------------------------|------|
| Lead-Free Process Capability | WAVE |
| Max-Temp | 260 |

This document was generated on Feb 12, 2024