


# multiple fittings and manifolds


## 3304 unequal multiple tee, with fixing holes



ØD1	ØD2		H	L1	$\frac{L}{2}$	N	T	$\Delta$ kg
6	4	3304 06 04	24,5	23	37	11,5	4,2	0,023
8	4	3304 08 04	24,5	23	37	11,5	4,2	0,031
8	6	3304 08 06	24,5	23	37	11,5	4,2	0,033
10	6	3304 10 06	36	29	40,5	14,5	4,2	0,058
10	8	3304 10 08	36	29	40,5	15,5	4,2	0,060

ØT = i.d. of fixing hole


## 3306 unequal multiple elbow, with fixing holes



ØD1	ØD2		G1	G2	H	L	N	T	$\Delta$ kg
6	4	3306 06 04	13,5	11	25	72	43	4,2	0,018
8	4	3306 08 04	13,5	11	25	73	43	4,2	0,032
8	6	3306 08 06	13,5	11	25	73	43	4,2	0,022
10	6	3306 10 06	16	13,5	31	84	52	4,2	0,056
10	8	3306 10 08	16	13,5	31,5	84	52	4,2	0,036


ØT = i.d. of fixing hole

## 3107 equal cross, with fixing holes




ØD			G	H	L	T	$\Delta$ kg
4		3107 04 00	11	36	20	4,2	0,010
6		3107 06 00	11	36	20	4,2	0,010
8		3107 08 00	13,5	46	22,5	4,2	0,020

## 3107 unequal cross, with fixing holes




ØD1	ØD2		G	H	L	T	$\Delta$ kg
4	6	3107 04 06	11	36	20	4,2	0,010
6	8	3107 06 08	13,5	46	22,5	4,2	0,020

This model provides 2 outlets ØD1 of equal diameters and 2 outlets ØD2 of a different diameter. ØT = i.d. of fixing hole




## 3107 unequal cross, with fixing holes




ØD1	ØD2		G	H	L	T	$\Delta$ kg
4	6	3107 06 04	11	36	20	4,2	0,010
6	8	3107 08 06	13,5	46	22,5	4,2	0,020

This model provides 3 outlets ØD1 of equal diameters and 1 outlet ØD2 of a different diameter. ØT = i.d. of fixing hole



## 3310 manifold with LF 3000® push-in connection



ØD	C		Number of outlets	E	H	L	L1	N	$\Delta$ kg
4	G1/4	3310 04 13	8	10	33	114	104	11,5	0,163
6	G1/4	3310 06 13	8	10	33	114	104	12,5	0,163
8	G3/8	3310 08 17	6	12	33	114	104	15	0,163
10	G1/2	3310 10 21	6	16	48	145,5	135,5	17,1	0,207
12	G1/2	3310 12 21	6	16	45	158	148	20,5	0,225