

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# DisplayPort 1.4 Cable (M/M) - UHD 8K, HDR, 4:2:0, HDCP 2.2, Latching Connectors, Black, 3 ft.

MODEL NUMBER: P580-003-V4









8K DisplayPort cable connects your DisplayPort 1.4-compatible source and display devices to transmit enhanced 8K UHD audio/video with HDR.

#### **Features**

DisplayPort 1.4 Cable Gets Your Gaming, Home Theater or Digital Signage Setup 8K-ReadyThis high-speed DisplayPort cable (M/M) securely connects source and display devices compatible with DisplayPort 1.4 audio/video signals. Backward compatible with all your existing DisplayPort devices, including Blu-ray players, game consoles and 4K televisions, the P580-003-V4 is ideal for future-proofing your high-definition or UHD A/V application in anticipation of an 8K upgrade. It flawlessly handles data transfer speeds up to 32 Gbps.

**Enjoy the Clarity of 4K/8K Video with 4:2:0 Color**The P580-003-V4 supports 8K UHD video resolutions up to 7680 x 4320 at 30 Hz. It's compatible with DisplayPort 1.4 standards for carrying HDR signals, which provide a wide range of vibrant colors with richer contrast, brighter whites and deeper blacks. HDCP 2.2 compliance and 4:2:0 chroma subsampling allow you to stream 4K Amazon and Netflix content with no complications.

Latching Connectors Help Prevent Accidental Disconnection and Expensive DowntimeHaving a cable come loose accidentally can mean costly and time-consuming signal loss. The latching DisplayPort connectors help you avoid such danger, protecting your audio/video transmission by maintaining a secure link without failure. The latching cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the cord always stays connected.

# **Highlights**

- Supports UHD resolutions up to 8K @ 30 Hz (4:2:0) for enhanced video without latency
- Supports High Dynamic Range (HDR) for richer contrast and expanded color accuracy
- Latching DisplayPort connectors prevent cable from coming loose accidentally
- Plug-and-play operation with no software required for easy, immediate installation

## **Applications**

- Watch 8K video from a compatible Blu-ray player, game console, laptop or tablet on a compatible television, monitor or projector
- Connect a Windows laptop to a conference table's A/V box to give a video presentation on a large screen
- Play online or PC video games that display optimal graphics
- Send 8K video content to digital signs or point-of-sale displays

### **System Requirements**

 Both source and display devices must be compatible with 8K standards to watch 8K video

#### Package Includes

P580-003-V4 DisplayPort 1.4
 Cable with Latching Connectors,
 8K, M/M, Black, 3 ft.

# **Specifications**

OVERVIEW	
UPC Code	037332255112
Product Type	Passive
Technology	DisplayPort





VIDEO		
Max Supported Video Resolution	7680 X 4320 30HZ (8K)	
Max Supported Color Depth	36-bit Deep Color	
HDR Support	Yes	
3D Video Supported	Yes	
Chroma Sub Sampling	4:2:0	
INPUT		
Bus Powered	Yes	
PHYSICAL		
Color	Black	
Material of Construction	PVC, ABS	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	4.8MM	
Wire Gauge (AWG)	32	
Cable Length (ft.)	3	
Cable Length (m)	0.9	
Cable Length (in.)	36	
Ferrite Core	No	
Shipping Dimensions (hwd / in.)	0.25 x 7.00 x 9.25	
Shipping Weight (kg)	0.06	
ENVIRONMENTAL		
Operating Temperature Range	32 TO 113 F (0 TO 45 C)	
Storage Temperature Range	14 TO 158 F (-10 TO 70 C)	
Operating Humidity Range	10% TO 85% RH, NON-CONDENSING	
Storage Humidity Range	5% TO 90% RH, NON-CONDENSING	
COMMUNICATIONS		
EDID Compatible	Yes	
Consumer Electronics Control (CEC) Supported	No	
CONNECTIONS		
Side A - Connector 1	DISPLAYPORT (MALE)	





Side B - Connector 1	DISPLAYPORT (MALE)	
Latching Connector	Yes	
Connector Plating	Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
Displayport Specification	1.4	
HDCP Specification	2.2	
Fully Molded Connector Ends	No	
Ohms	No	
EMI/RFI Line Noise Protection	No	
Integral Strain Relief	No	
Impedance-Matched Twisted-Pair Construction	No	
DIN Mountable	No	
Integrated/Removable Cable	No	
MST Support	No	
Scaler Function	No	
IP67 Rated	No	
STANDARDS & COMPLIANCE		
Certifications	RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>