

This document was generated on 03/20/2023 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	5023520510			
0020020010			EU ELV	
	Active			
Overview:			Compliant	
Description:		der, Single Row, Right-Angle, 5 Circuits, Gold (Au) Plating,	EU RoHS	China RoHS
	Natural		Compliant	
			REACH SVHC	
Agency Certification			Not Contained per -	
UL		E29179	D(2022)9120-DC (17	7
02		220110	Jan 2023)	
General			Halogen-Free	
Product Family		PCB Headers	Status	
Series		<u>502352</u>	Not Low-Halogen	
Application		Automotive, Signal, Wire-to-Board		n, please visit <u>Contact US</u>
Comments		The Operating Temperature Range when used with		, please visit <u>contact co</u>
		DuraClik series 502351 is -40°C to +105°C. It is -40°C	China ROHS	Green Image
		to 125°C when used with DuraClik ISL series 560123 or	ELV	Compliant
		TPA series 505151.	RoHS Phthalates	Not Contained
Component Type		PCB Header		
Overview		duraclik		
Product Name		DuraClik		
Taxonomy		PCB Headers and Receptacles	Search Parts in th	nis Series
UPC		884982861886	502352 Series	
UFC		004902001000		
Physical			Mates With	
Breakaway		No		ousings <u>502351</u> , <u>560123</u> ,
Circuits (Loaded)		5	505151	<u>domigo <u>dozobi</u>, <u>dobizo</u>,</u>
Circuits (maximum)		5		
Color - Resin		Natural		
Durability (mating cycle	e max)	30		
First Mate / Last Break		No		
Flammability		SC-0		
Glow-Wire Capable		No		
Keying to Mating Part		Yes		
Lock to Mating Part		Yes		
Ũ		6.40mm		
Mated Height				
Material - Metal Material - Plating Matin	_	Copper Alloy		
Ū.	ig	Gold		
Material - Resin		Polyamide		
Net Weight		0.664/g		
Number of Rows		l Diabt Apalo		
Orientation		Right Angle		
PCB Locator		No		
PCB Retention		Yes		
Packaging Type		Embossed Tape on Reel		
Pitch - Mating Interface		2.00mm		
Polarized to Mating Pa	rt	Yes		
Polarized to PCB		Yes		
Stackable		No		
Temperature Range - 0		-40° to +105°C		
Termination Interface:	Style	Surface Mount		
Electrical				
Current - Maximum per		3.0A		
	Contact	125V		
Voltage - Maximum		1207		
Solder Process Data				
Duration at Max. Proce	ess Temperature (seconds)	040		
Lead-freeProcess Capa		REFLOW		
1	2			

Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	255

Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

5051510002-000, PS-502351-002-001 SD-502352-001-001, SD-502352-002-001

This document was generated on 03/20/2023 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION