

This document was generated on 01/17/2019

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 0015247240

Status: **Active** 

Overview: Mini-Fit Products

**Description:** Mini-Fit BMI Receptacle Header, 4.20mm Pitch, Dual Row, Vertical, with Snap-In

Plastic Pegs, Post 2.54µm Tin (Sn), UL 94V-2, 24 Circuits

**Documents:** 

3D Model Packaging Specification PK-42385-999 (PDF) **Drawing (PDF)** Test Summary 423850000-TS-000 (PDF) Product Specification PS-5556-002-001 (PDF) RoHS Certificate of Compliance (PDF)

Product Specification TS-5556-002-001 (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

**PCB** Receptacles **Product Family** 

Series 42385

Application Board-to-Board, Power

Solder Type|With Pegs, Solder Type|With Pegs Comments

Trav

Mini-Fit Products Overview **Product Name** Mini-Fit BMI **UPC** 800753535060

**Physical** 

Circuits (Loaded) 24 Circuits (maximum) 24 Color - Resin Natural Durability (mating cycles max) 30 Flammability 94V-2 Glow-Wire Capable No Guide to Mating Part Yes Keying to Mating Part None Lock to Mating Part None Material - Metal **Brass** Material - Plating Mating Tin Material - Resin Nylon Net Weight 4.843/g Number of Rows Orientation Vertical **PCB** Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.20mm

Pitch - Mating Interface 4.20mm Pitch - Termination Interface 4.20mm Polarized to Mating Part Yes Polarized to PCB Yes Surface Mount Compatible (SMC) No

Temperature Range - Operating -40° to +105°C Termination Interface: Style Through Hole

**Electrical** 

Packaging Type

9.0A Current - Maximum per Contact Grounding to PCB

Voltage - Maximum 600V AC (RMS)/DC



## **EU ELV**

**Not Relevant** 

**EU RoHS China RoHS** 

Compliant

**REACH SVHC** 

Not Contained Per -ED/61/2018 (27 June

2018)

**Halogen-Free** 

**Status** 

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image **ELV** Not Relevant **RoHS Phthalates** Not Contained

## Search Parts in this Series

42385 Series

## **Mates With**

42475 Panel Mount Plug, 42404 Right Angle Header, 42440 Vertical Header, 43879 Vertical Header, 44068 Vertical Header

**Solder Process Data** 

Duration at Max. Process Temperature (seconds) 005 Lead-freeProcess Capability WAVE Max. Cycles at Max. Process Temperature 001 Process Temperature max. C 240

**Material Info** 

**Engineering Number** 42385-24A1

**Reference - Drawing Numbers** 

Packaging Specification PK-42385-999

**Product Specification** PS-5556-002-001, TS-5556-002-001

Sales Drawing SDA-42385-X Symbol/Footprint Data SYM-A42385-24XX **Test Summary** 423850000-TS-000

This document was generated on 01/17/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION