160762-2 - ACTIVE

FASTIN-FASTON | FASTIN-FASTON 110

TE Internal #: 160762-2 Quick Disconnects, Tab, 20 – 15 AWG Wire Size, .51 – 1.65 mm² Wire Size, Mating Tab Width 2.8 mm [.11 in], Straight, FASTIN-FASTON 110

View on TE.com >

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: Tab

Wire Size: .51 – 1.65 mm²

Mating Tab Width: 2.8 mm [.11 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features



| Insertion Force | Normal | | | | | | |
|-----------------------------------|-----------------|--|--|--|--|--|--|
| Configuration Features | | | | | | | |
| Connection Capacity | Single | | | | | | |
| Compatible With Wire & Cable Type | Discrete Wire | | | | | | |
| Contact Features | | | | | | | |
| Quick Disconnect Terminal Type | Tab | | | | | | |
| Mating Tab Width | 2.8 mm[.11 in] | | | | | | |
| Mating Tab Thickness | .81 mm[.032 in] | | | | | | |
| Terminal Orientation | Straight | | | | | | |
| Contact Base Material | Phosphor Bronze | | | | | | |
| Terminal Plating Material | Pre-Tin | | | | | | |
| Crimp Type | F-Crimp | | | | | | |
| Barrel Type | Open | | | | | | |
| Termination Features | | | | | | | |

C For support call+1 800 522 6752

160762-2

Quick Disconnects, Tab, 20 – 15 AWG Wire Size, .51 – 1.65 mm² Wire Size, Mating Tab Width 2.8 mm [.11 in], Straight, FASTIN-FASTON 110



| Product Terminates To | Wire & Cable |
|--------------------------------------|-----------------------------|
| Mechanical Attachment | |
| | .055 in |
| Wire Insulation Support | With |
| Mating Retention Type | Locking Lance |
| Dimensions | |
| Terminal Material Thickness | .41 mm[.016 in] |
| Product Length | 22 mm[.866 in] |
| Compatible Insulation Diameter Range | 2.31 – 3 mm[.091 – .118 in] |
| Wire Size | .51 – 1.65 mm² |
| Usage Conditions | |
| Insulation Option | Uninsulated |
| Operating Temperature Range | -40 - 110 °C[-40 - 230 °F] |
| Packaging Features | |
| Packaging Quantity | 6000 |
| Packaging Method | Strip/Reel |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

160762-2

Quick Disconnects, Tab, 20 – 15 AWG Wire Size, .51 – 1.65 mm² Wire Size, Mating Tab Width 2.8 mm [.11 in], Straight, FASTIN-FASTON 110



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts



Also in the Series | FASTIN-FASTON 110



| Automotive Housings(6) | Automotive Terminals(6) | Crimp Terminal Housings(34) | Insertion & Extraction Tools(3) |
|------------------------|-------------------------|-----------------------------|---------------------------------|
| | | | |
| | | | |



Customers Also Bought

160762-2

Quick Disconnects, Tab, 20 – 15 AWG Wire Size, .51 – 1.65 mm² Wire Size, Mating Tab Width 2.8 mm [.11 in], Straight, FASTIN-FASTON 110





Documents

Product Drawings FF 110 TAB 0.5-1.5MM2 PTPBR

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_160762-2_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160762-2_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160762-2_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications FASTIN-FASTON CONN. .110 INCH, .187 INCH, .250 INCH, .375 INCH SRS.

English

Product Specification

English