


RK10J With Knob Type

Low-profile type compatible with reflow soldering



Typical Specifications



Items	Specifications
Total resistance tolerance	±30%
Maximum operating voltage	50V AC, 20V DC (Single-unit only)
Total rotational angle	270° ± 10°
Rotational torque	0.5 to 10mN·m
Operating life	10,000 cycles
Operating temperature range	-10°C to +60°C

Product Line


Number of resistor elements	Mounting method	Mounting type	Knob type	Total resistance (k Ω)	Resistance taper	For DC use	Minimum order unit (pcs.)		Products No.	Drawing No.
							Japan	Export		
Single-unit	Manual	Insertion (2mm)	Knob diameter : φ 14 Knob thickness : t0.9 Color : Black	10	1B	20V DC	3,000	2,400	RK10J11E0034	1
Dual-unit					15A	Not applicable				
Single-unit	Reflow	Surface mounting	Knob diameter : φ 14 Knob thickness : t1.0 Color : Black		1B	20V DC	3,000	3,000	RK10J11R0A0L	2
Dual-unit					15A	Not applicable				

Notes Other varieties are also available. Refer to "Other Specifications" (P.338, 339).

Packing Specifications

Bulk / Taping

Mounting method	Packing specifications	Number of packages (pcs.)			Tape width (mm)	Export package measurements (mm)
		1 reel	1 case /Japan	1 case /export packing		
Manual	Bulk	—	3,000	2,400	—	371×250×190
Reflow	Taping	1,000	3,000	3,000	24	401×397×139



Dimensions

No.	Photo	Style	PC board mounting hole dimensions (Viewed from mounting side)
1	<p>RK10J1 □ E Manual</p>		

Refer to P.338 for other specifications.
Refer to P.340 for ordering products not listed.
Refer to P.341 for soldering conditions.

RK10J With Knob Type

Dimensions

Unit:mm

No.	Photo	Style	PC board mounting hole dimensions (Viewed from mounting side)
2	<p>RK10J1 □ R Reflow</p>		<p>Center of knob</p> <p>Shaded area: Solder land</p>

Circuit Diagram

Single-unit	Dual-unit	Dual-unit resistance taper 15C

With Knob Type / Other Specifications

In addition to the Product Line, we accommodate the following specifications. Combinations not included in the Product Line are treated as semi-standard products.

Total Resistance Variety

Total resistance (k Ω)	10	20	50	100

Resistance Taper

Resistance taper	15A	1B	3B	15C

Terminal Layout

	Resistance taper A or B		Resistance taper C	
	Single-unit	Dual-unit	Single-unit	Dual-unit
10mm Single-unit/ Dual-unit RK10J1 □ E (Manual)				
10mm Single-unit/ Dual-unit RK10J1 □ R (Reflow)				

Refer to P.340 for ordering products not listed.


With Knob Type / Other Specifications

In addition to the Product Line, we accommodate the following specifications. Combinations not included in the Product Line are treated as semi-standard products.

■ Mounting Plate Types and Terminal Types

RK10J1 □ E (Manual)		Unit:mm
Terminal length : 2.0	Terminal length : 2.8	

■ Knob Variety



Applicable models	Knob variety			Body thickness (mm)
	Type	Outer diameter D	Thickness (mm)	
RK10J11E RK10J12E (Manual)	K4	$\phi 14$	0.9	Black
	K5	$\phi 16$	3.0	
RK10J11R RK10J12R (Reflow)	K1	$\phi 14$	1.0	Black
	K2	$\phi 14$	2.5	
	K3	$\phi 16$		

Note

Marked are specifications recommended by Alps Alpine.

Rotary
Potentiometers

Slide
Potentiometers

Metal Shaft

Insulated
Shaft

Knob
Operating

Through
Shaft Type

Ring Type

With Knob Type / Ordering Products Not Listed

In addition to the Product Line, we accommodate the following specifications. Combinations not included in the Product Line are treated as semi-standard products. Please refer to the notation example below.

Sample Part Number

R K 1 0 J 1 1 R — **K 1** — **B 2 0 3**

Model type

Code	Model type
RK10J11E	10mm size single-unit Manual
RK10J12E	10mm size dual-unit Manual
RK10J11R	10mm size single-unit Reflow
RK10J12R	10mm size dual-unit Reflow

Shaft type (Outer diameter/Thickness) (mm)



Code	RK10J1□E	RK10J1□R
K1	—	V14 t1.0
K2	—	V14 t2.5
K3	—	V16 t2.5
K4	V14 t0.9	—
K5	V16 t3.0	—

*Color : Black

Resistance taper

Code	Resistance taper	Code	Resistance taper
A	15A	C	15C
B	1B	V	3B

B: For tone & general
V: For vol.



Total resistance

Code	Total resistance (k Ω)	Code	Total resistance (k Ω)
103	10	503	50
203	20	104	100

Note

Marked are specifications recommended by Alps Alpine.

Rotary Potentiometers

Slide Potentiometers

Metal Shaft

Insulated Shaft







Knob Operating

Through Shaft Type

Ring Type

Knob Operating Type Potentiometers

List of Varieties

Type	Without knob type		With knob type	
Series	RK08H1 □ 1	RK08H1 □ 3	RK10J1 □ E	RK10J1 □ R
	Single-unit/Dual-unit	Single-unit/Dual-unit	Single-unit/Dual-unit	Single-unit/Dual-unit
Photo				
Terminal orientation	Vertical	Reflow type	—	—
Operating temperature range	-10°C to +60°C			
Operating life	Without detent 10,000 cycles With detent 5,000 cycles		10,000 cycles	
Automotive use	—	—	—	—
Life cycle				
Electrical performance	Total resistance (k Ω)	5, 10, 20, 50, 100		10, 20, 50, 100
	Resistance taper	15A, 1B, 3B, 15C		
	Rated power	0.03W		
	Insulation resistance	—	—	100MΩ min. 100V DC
	Voltage proof	—	—	100V AC for 1minute
Mechanical performance	Detent	Without / Center detent		Without
	Stopper strength	0.1N		70mN·m
	Push-pull strength	10N		5N
Terminal style	Insertion	Reflow	Insertion	Reflow
Page	333		337	

Residual Resistance

※ Applies only to products with specified residual resistance

Nominal total resistance	※ Residual resistance
100kΩ ≥ R ≥ 50kΩ	0.1% or less of nominal total resistance
50kΩ > R > 10kΩ	30Ω or less
10kΩ ≥ R	20Ω or less

Maximum Attenuation

Nominal total resistance	Maximum attenuation
R ≥ 100kΩ	90dB min.
100kΩ > R ≥ 50kΩ	80dB min.
50kΩ > R ≥ 10kΩ	70dB min.
10kΩ > R	60dB min.


Knob Operating Type Potentiometers Soldering Conditions	341
Potentiometers Cautions	384
Potentiometers Measurement and Test Methods	386
Potentiometers Resistance Taper	388

Reference for Manual Soldering

Series	Tip temperature	Soldering time	No. of solders
RK08H1□1, RK10J	350°C max.	3s max.	1 time

Example of Reflow Soldering Condition

Temperature profile



Series	A	B	C	D	E	F	G	H	No. of reflows
RK08H1□3, RK10J1□R	250°C	200°C	150°C	150°C	2 min.	3s	40s	4 min.	2 time max.

Notes

1. When using an infrared reflow oven, solder may sometimes not be applied. Be sure to use a hot air reflow oven or a type that uses infrared rays in combination with hot air.
2. The temperatures given above are the maximum temperatures at the terminals of the potentiometer when employing a hot air reflow method. The temperature of the PC board and the surface temperature of the potentiometer may vary greatly depending on the PC board material, its size and thickness. Ensure that the surface temperature of the potentiometer does not rise to 250°C or greater.
3. Conditions vary to some extent depending on the type of reflow bath used. Be sure to give due consideration to this prior to use.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Alps Alpine:

[RK10J12E0A0A](#) [RK10J12E002L](#) [RK10J12E0024](#) [RK10J11R0A0H](#) [RK10J12R0A0B](#) [RK10J12R0052](#)
[RK14J11A000G](#) [RK14J11A0A02](#) [RK14J12A0A0K](#) [RK14J11R000H](#) [RK14J12R0A01](#) [RK14J12R0A0C](#)
[RK14J12R0A09](#) [RK10J11E0034](#) [RK10J11E002Y](#) [RK10J11R001Y](#) [RK14J11A0007](#) [RK14J11R000J](#) [RK14J12A0A0U](#)
[RK10J12R0A02](#)