



This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

MARKETING SALES DRAWING
DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING
DIMENSIONS IN METRIC - []



Electrical Testing
per Tusonix standard
test plans and Mil-Std-202
Test Methods.



NOTES:

1. TUSONIX STANDARD PART NUMBER: 7602-501. TUSONIX RoHS COMPLIANT PART NUMBER: 7602-501 LF. CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
2. LEAD FINISH: MATTE TIN.
3. PLATE MATERIAL: COPPER ALLOY, MATTE TIN FINISH.
4. PART MARKING: PART NUMBER, DATE CODE AND UL RECOGNITION: WHITE INK. RoHS PART: GREEN INK DOT ON TOP OF GROUND PLATE AS SHOWN.
5. MAX. SOLDERING TEMPERATURE 500°F [260°C].
6. BLOCK MOUNTING: RECOMMENDED MOUNTING SCREWS (# 8 PAN HEAD). TORQUE 4.5-5.5 in. lbs. [0.51-0.62 Nm] MAX.
7. MOLDED MATERIAL: HIGH TEMPERATURE THERMOPLASTIC (PBT), UL RATED 94 V-O.
8. U.L. FILE NO. E201344.

Cx (pF)	WORKING VOLTAGE -40°C TO +125°C	I _{DC}	I.R. MIN. @ 100 (VDC.)	DWV (VAC)	TYPICAL NO LOAD INSERTION LOSS (dB) @ 25°C PER MIL-STD-220			
					10 MHz	100 MHz	1 GHz	10 GHz
2000 MIN.	250 VAC	20 Amps	10 G Ω	1500	5	50	60	65

REVISION RECORD	Original Release	Title FILTERED TERMINAL BLOCK 2 POSITION, UL RECOGNIZED	TOLERANCES unless otherwise specified	
	C.O. 19990607-1-06		2 PLC. DECIMAL ± N/A	
	REVISED BLOCK & NOTE 3. ADDED NOTE 5. S.M. 01-28-00		3 PLC. DECIMAL ± .030 [0.76]	
	20000127-3-01		ANGLES ± N/A	
	ADDED DWV & I.R. REVISED NOTES & METRIC. S.M. 06-15-04		Drawn S.M. 06-08-99	Scale FULL
	20040615-1-07		Approved T.C. 06-08-99	
20040628-5-05	TUSONIX	A	7602-501	
ADDED NOTES 1-4 & RENUMBERED. S.M. 10-12-05	TUCSON, ARIZONA			
20050926-5-09				
NOTES REVISED. L.E. 10-25-05				
20051025-1-01				
NOTES 4 & 6 REVISED. ADDED INK DOT. REVISED TORQUE. S.M. 01-20-06				
20060103-1-01				

X-2015 Rev-0

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tusonix / CTS:](#)

[7602-501LF](#)