

Overhead Door Magnetic Contacts

SM-226LQ 2³/₄" (70mm) Gap, Closed loop, UL listed

SM-226L-3Q 2³/₄" (70mm) Gap, Open/Closed loop

Features:


- Used for overhead doors in both industrial and residential situations where a wide gap is present
- Adjustable to fit most door-channel widths
- Switch contained in curved low-profile cast-aluminum housing for surface mounting on garage floor
- Magnet enclosed in gray ABS case on L-bracket
- 24" (61cm) wire leads enclosed in armored cable
- Contact reed switch is SPST, deactivated rhodium on gold underplating for a longer expected life
- For closed loop circuits (SM-226LQ)
- For open/closed loop circuits (SM-226L-3Q)
- 2³/₄" (70mm) Gap
- Mounting bracket included
- Limited lifetime warranty



SM-226LQ Shown




SM-226LQ Only



Specifications:

Model	SM-226LQ	SM-226L-3Q
Loop type	Closed loop	Open/Closed loop
Electrical config.	N/O	SPDT
Operation gap	2 ³ / ₄ " (70mm)	
Material	Switch	Heavy-duty cast-aluminum case
	Terminal	24" (61cm) armored leads
	Magnet	ABS plastic on L-bracket
Contacts	Deactivated rhodium on gold underplating	
Contact rating	0.1A@100VDC (max)	0.02A@100VDC (max)
	1.0A@10VDC (max)	0.2A@10VDC (max)
	10W (max)	3W (max)
Temperature	-15°~160° F (-25°~70° C)	
Switch cycles	50 Million (0.1mA@5VDC)	
Switch dimensions	4 ⁵ / ₁₆ "x1 ³ / ₄ "x7 ¹ / ₁₆ " (110x44x11mm)	
Magnet dimensions	3 ¹⁵ / ₁₆ "x2"x2" (100x51x51mm)	
Magnet type	Alnico 5	

Dimensions:



Note: On wood surfaces, the magnet shall be installed at least 1/4" (25.4mm) from the switch housing to comply with UL 681 installation requirements

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

Copyright © 2017 SECO-LARM U.S.A., Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PI_SM-226Lseries_170717.docx