



REVISIONS											
REV	ECO	DESCRIPTION	DATE	BY	APPR						
A1	-	RELEASE NUMBER	14/JUN/2021	LOUIE	TOMMY						




22.2









PROTECTIVE COVER FOR 12,15,18-WAY PLUG

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: THERMOPLASTIC, COLOR: BLACK

2. RoHS COMPLIANT

3. MOISTURE RESISTANCE: IP69K & IP68 (1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION)

- 4. TEMPERATURE RANGE: -55°C~125°C
- 5. USE WITH CONNECTORS AT06-12S* & AT16-15S* & AT16-18S* (* = MODIFICATIONS AND/OR COLORS)
- 6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

	AT16-1518S-CAP			REF:1011-349-1205					
PART NUMBER			2	DESCRIPTION					
QUANTITY MATERIALS LIST									
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Toteranos are as follows: 1 PL DEC 40.30 3) Note reference = X		SIGNATURES		DATE	Amphonol				
		DRAWN:	LOUIE.YIN	14JUN2021	Amphenol				
		CHECKED:	ORION.LI	15JUN21	Sine Systems - www.amphenol-sine.com				
		ENGINEER:			44724 Morley Drive				
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMYXIE	16JUN21			Clinton Township, MI 48036		
PROCESS SPECIFICATIONS: NEXT ASSY:		CUSTOMER:			PROTECTIVE COVER FOR 12,15,18-WAY PLUG				
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SILBIECT TO NORMAL							
					В	C-	AT16-1518S-CAP	A1	
		MANUFACTURING VARIATIONS.		SCALE: N	ONE	SHEET 1 C	F 1		