

Product data sheet

Specifications



Residual current circuit breakers (RCBOs)

AVDT-63M EKF PROXIMA

IEC 61009-1

Product line	PROXIMA
Series name	AVDT-63M
Device application	Distribution
Product type	Residual current circuit breaker
Rated voltage [Ue, V]	230
Frequency [Hz]	50/60
Poles	1P+N
Width [mm]	18
Rated current [In, A]	6, 10, 16, 20, 25, 32, [40]
Rated breaking residual current [IΔn, mA]	10, 30, 100
Residual current trip type	A, AC
Tripping curve	B, C
Breaking capacity [Icn, A]	6 000
Rated residual non-operating current [IΔno, mA]	0,5IΔn
Energy limiting class	3
Mechanical endurance, O-C cycles	10 000
Electrical endurance, O-C cycles	4 000
Tightening torque, max. [N·m]	1,2
Degree of protection	IP20
Operating temperatures [°C]	-25 ... +55
Cross-section of connection wires [mm ²]	1 - 25
Contact position indicator	Yes
Auxiliaries	No
Mounting support	DIN rail
Weight, max. [kg]	0,2
Standard	IEC 61009-1
Color	Grey (RAL 7035/Pantone Cool Gray 2C)
Warranty period	7 years



EKF

EKF ELECTRICAL SOLUTION – FZCO
Dubai Silicon Oasis, DDP, Building A2,
Dubai, United Arab Emirates
P.O. Box 342001

www.global.ekfgroup.com

**ENERGY
KNOWLEDGE
FUTURE**

Overall dimensions:

