

Type CG Reliable Screw Terminal Aluminum Electrolytic Capacitor

85 °C, Screw Terminal Capacitors



Type CG screw terminal, aluminum electrolytic capacitors have excellent reliability and are good for 2000 hours at 85 °C at full rated voltage.

Highlights

- High reliability at 85 °C
- Screw Terminal
- Long Life

[RoHS Compliant](#)

Specifications

| | |
|------------------------------------|---|
| Capacitance Range: | 40 to 160,000 µF |
| Voltage Range: | 10 to 450 WVdc |
| Capacitance Tolerance: | -10% +75% (10 - 150 WVdc) -10% +50% (151 - 450 WVdc) |
| Operating Temperature: | -40 °C to +85 °C |
| Ripple Current Multipliers: | Ambient Temperature |

| 25 °C | 35 °C | 45 °C | 55 °C | 65 °C | 85 °C |
|-------|-------|-------|-------|-------|-------|
| 2.00 | 1.88 | 1.72 | 1.58 | 1.42 | 1.00 |

| Rated Voltage | Ripple Multiplier | | | | |
|---------------|-------------------|--------|---------|---------|--------|
| | 120 Hz | 400 Hz | 1000 Hz | 2500 Hz | 10 kHz |
| 10 to 75 | 1.000 | 1.050 | 1.085 | 1.135 | 1.150 |
| 76 to 250 | 1.000 | 1.075 | 1.125 | 1.155 | 1.210 |
| 251 to 450 | 1.000 | 1.080 | 1.130 | 1.175 | 1.230 |

DC Leakage Current: $I \leq 3 \sqrt{CV}$ after 5 minutes

Not to exceed 4.0 mA

C = Capacitance in µF

V = Rated Voltage

I = Leakage current in µA

[Click here to see: Hardware & Mounting Options](#)

QA Stability Test: Apply WVdc for 2000 h @ 85 °C

- Capacitance change ±15% from initial limits
- DC leakage current: 200% of limit
- ESR: 175% of limit

[Click here to see: Mechanical Details](#)

Ratings

| Cap (µF) | Catalog Part Number | Typical ESR | | Max Ripple | |
|---------------------------------|------------------------|---------------|-----------------------------|--------------------|--------------------|
| | | 120 Hz (Ω) | 120 Hz +85 °C (A) RMS | 120 Hz (Inches) | Length (Inches) |
| 10 WVdc (15 Vdc Surge) | | | | | |
| 160,000 | CG164U010X5L | 0.006 | 27.1 | 3 | 5.625 |
| 16 WVdc (20 Vdc Surge) | | | | | |
| 2,500 | CG252U016R2C | 0.047 | 3.9 | 1.375 | 2.125 |
| 6,500 | CG652U016R2C | 0.039 | 4.3 | 1.375 | 2.125 |
| 10,500 | CG1052U016V3C | 0.027 | 7.6 | 2.000 | 3.125 |

| Cap (µF) | Catalog Part Number | Typical ESR | | Max Ripple | |
|---------------------------------|------------------------|---------------|-----------------------------|--------------------|--------------------|
| | | 120 Hz (Ω) | 120 Hz +85 °C (A) RMS | 120 Hz (Inches) | Length (Inches) |
| 16 WVdc (20 Vdc Surge) | | | | | |
| 12,000 | CG123U016R3C | 0.024 | 6.4 | 1.375 | 3.125 |
| 18,000 | CG183U016R4C | 0.018 | 8.3 | 1.375 | 4.125 |
| 21,000 | CG213U016U3C | 0.012 | 10.5 | 1.750 | 3.125 |
| 27,000 | CG273U016V3C | 0.012 | 11.4 | 2.000 | 3.125 |
| 40,000 | CG403U016V4C | 0.009 | 14.7 | 2.000 | 4.125 |

Type CG Reliable Screw Terminal Aluminum Electrolytic Capacitor

Ratings

| Cap (µF) | Catalog Part Number | Typical | | Max Ripple | |
|----------------------------------|------------------------|----------------------|-----------------------------|------------------|--------------------|
| | | ESR 120 Hz (Ω) | 120 Hz +85 °C (A) RMS | Dia. (Inches) | Length (Inches) |
| 25 WVdc (40 Vdc Surge) | | | | | |
| 1,500 | CG152U025R2C | .058 | 3.5 | 1.375 | 2.125 |
| 2,800 | CG282U025R3C | 0.036 | 5.2 | 1.375 | 3.125 |
| 3,300 | CG332U025R2C | 0.043 | 4.1 | 1.375 | 2.125 |
| 4,500 | CG452U025U3C | 0.006 | 14.8 | 1.750 | 3.125 |
| 6,000 | CG602U025V3C | 0.029 | 7.3 | 2.000 | 3.125 |
| 6,300 | CG632U025R3C | 0.028 | 5.9 | 1.375 | 3.125 |
| 8,500 | CG852U025V4C | 0.022 | 9.4 | 2.000 | 4.125 |
| 9,200 | CG922U025R4C | 0.022 | 7.5 | 1.375 | 4.125 |
| 10,000 | CG103U025U3C | 0.026 | 7.1 | 1.750 | 3.125 |
| 13,000 | CG133U025V3C | 0.024 | 8.0 | 2.000 | 3.125 |
| 20,000 | CG203U025V4C | 0.019 | 10.1 | 2.000 | 4.125 |
| 20,000 | CG203U025X4C | 0.019 | 12.9 | 3.000 | 4.125 |
| 32,000 | CG323U025W4C | 0.010 | 15.9 | 2.500 | 4.125 |
| 48,000 | CG483U025X4C | 0.005 | 25.2 | 3.000 | 4.125 |
| 35 WVdc (50 Vdc Surge) | | | | | |
| 1,100 | CG112U035R2C | 0.063 | 3.4 | 1.375 | 2.125 |
| 2,100 | CG212U035R3C | 0.039 | 5.0 | 1.375 | 3.125 |
| 2,300 | CG232U035R2C | 0.051 | 3.8 | 1.375 | 2.125 |
| 4,300 | CG432U035R3C | 0.030 | 5.7 | 1.375 | 3.125 |
| 9,500 | CG952U035V3C | 0.025 | 7.9 | 2.000 | 3.125 |
| 11,000 | CG113U035W4C | 0.021 | 11.0 | 2.500 | 4.125 |
| 11,000 | CG113U035U4C | 0.020 | 9.1 | 1.750 | 4.125 |
| 14,000 | CG143U035V4C | 0.018 | 10.4 | 2.000 | 4.125 |
| 22,000 | CG223U035W4C | 0.011 | 15.2 | 2.500 | 4.125 |
| 33,000 | CG333U035X4C | 0.006 | 23.0 | 3.000 | 4.125 |
| 50 WVdc (75 Vdc Surge) | | | | | |
| 800 | CG801U050R2C | 0.072 | 3.2 | 1.375 | 2.125 |
| 1,500 | CG152U050R2C | 0.058 | 3.5 | 1.375 | 2.125 |
| 1,500 | CG152U050R3C | 0.044 | 4.7 | 1.375 | 3.125 |
| 2,000 | CG202U050R4C | 0.033 | 6.1 | 1.375 | 4.125 |
| 2,500 | CG252U050U3C | 0.037 | 6.0 | 1.750 | 3.125 |
| 2,900 | CG292U050R3C | 0.036 | 5.2 | 1.375 | 3.125 |
| 3,300 | CG332U050V3C | 0.035 | 6.7 | 2.000 | 3.125 |
| 4,300 | CG432U050R4C | 0.026 | 6.9 | 1.375 | 4.125 |
| 4,500 | CG452U050V4C | 0.026 | 8.6 | 2.000 | 4.125 |
| 5,000 | CG502U050U3C | 0.029 | 6.7 | 1.750 | 3.125 |
| 6,500 | CG652U050V3C | 0.017 | 9.6 | 2.000 | 3.125 |
| 7,300 | CG732U050W4C | 0.023 | 10.5 | 2.500 | 4.125 |
| 7,400 | CG742U050U4C | 0.022 | 8.7 | 1.750 | 4.125 |
| 9,500 | CG952U050V4C | 0.013 | 12.2 | 2.000 | 4.125 |
| 10,000 | CG103U050X4C | 0.013 | 15.6 | 3.000 | 4.125 |
| 15,000 | CG153U050W4C | 0.009 | 16.8 | 2.500 | 4.125 |
| 16,500 | CG1652U050X5L | 0.010 | 20.5 | 3.000 | 5.625 |
| 22,000 | CG223U050X4C | 0.006 | 22.5 | 3.000 | 4.125 |
| 33,000 | CG333U050X5L | 0.005 | 29.0 | 3.000 | 5.625 |
| 75 WVdc (100 Vdc Surge) | | | | | |
| 600 | CG601U075R2C | 0.085 | 2.9 | 1.375 | 2.125 |
| 800 | CG801U075R2C | 0.072 | 3.2 | 1.375 | 2.125 |
| 1,000 | CG102U075R3C | 0.053 | 4.3 | 1.375 | 3.125 |
| 1,500 | CG152U075R4C | 0.037 | 5.8 | 1.375 | 4.125 |
| 1,500 | CG152U075R3C | 0.045 | 4.7 | 1.375 | 3.125 |
| 2,000 | CG202U075U3C | 0.039 | 5.8 | 1.750 | 3.125 |
| 2,500 | CG252U075V3C | 0.036 | 6.6 | 2.000 | 3.125 |
| 2,600 | CG262U075U3C | 0.035 | 6.1 | 1.750 | 3.125 |

| Cap (µF) | Catalog Part Number | Typical | | Max Ripple | |
|-----------------------------------|------------------------|----------------------|-----------------------------|------------------|--------------------|
| | | ESR 120 Hz (Ω) | 120 Hz +85 °C (A) RMS | Dia. (Inches) | Length (Inches) |
| 75 WVdc (100 Vdc Surge) | | | | | |
| 3,300 | CG332U075V3C | 0.022 | 8.4 | 2.000 | 3.125 |
| 3,450 | CG3451U075V4C | 0.027 | 8.5 | 2.000 | 4.125 |
| 4,900 | CG492U075V4C | 0.015 | 11.3 | 2.000 | 4.125 |
| 7,900 | CG792U075W4C | 0.012 | 14.5 | 2.500 | 4.125 |
| 8,200 | CG822U075X4C | 0.012 | 16.3 | 3.000 | 4.125 |
| 11,000 | CG113U075X4C | 0.009 | 18.8 | 3.000 | 4.125 |
| 12,500 | CG1252U075X5L | 0.009 | 21.8 | 3.000 | 5.625 |
| 100 WVdc (135 Vdc Surge) | | | | | |
| 400 | CG401U100R2C | 0.180 | 2.0 | 1.375 | 2.125 |
| 1,000 | CG102U100R4C | 0.068 | 4.3 | 1.375 | 4.125 |
| 1,300 | CG132U100U3C | 0.066 | 4.5 | 1.750 | 3.125 |
| 1,700 | CG172U100W4C | 0.050 | 5.7 | 1.750 | 4.125 |
| 2,250 | CG2251U100V4C | 0.036 | 7.3 | 2.000 | 4.125 |
| 2,500 | CG252U100V4C | 0.030 | 8.0 | 2.000 | 4.125 |
| 3,600 | CG362U100W4C | 0.020 | 11.3 | 2.500 | 4.125 |
| 4,000 | CG402U100W4C | 0.019 | 11.5 | 2.500 | 4.125 |
| 150 WVdc (185 Vdc Surge) | | | | | |
| 275 | CG2750U150R2C | 0.170 | 2.1 | 1.375 | 2.125 |
| 500 | CG501U150R3C | 0.103 | 3.1 | 1.375 | 3.125 |
| 1,550 | CG1551U150V4C | 0.052 | 6.1 | 2.000 | 4.125 |
| 2,500 | CG252U150W4C | 0.030 | 9.2 | 2.500 | 4.125 |
| 3,600 | CG362U150X4C | 0.022 | 9.4 | 3.000 | 4.125 |
| 5,600 | CG562U150X3L | 0.014 | 17.0 | 3.000 | 3.625 |
| 200 WVdc (250 Vdc Surge) | | | | | |
| 180 | CG181T200R2C | 0.280 | 1.6 | 1.375 | 2.125 |
| 450 | CG451T200R4C | 0.120 | 3.2 | 1.375 | 4.125 |
| 550 | CG551T200U3C | 0.150 | 3.0 | 1.750 | 3.125 |
| 750 | CG751T200V3C | 0.102 | 3.9 | 2.000 | 3.125 |
| 1,000 | CG102T200V4C | 0.085 | 4.8 | 2.000 | 4.125 |
| 1,650 | CG1651T200W4C | 0.050 | 7.8 | 2.500 | 4.125 |
| 2,450 | CG2451T200X4C | 0.034 | 9.7 | 3.000 | 4.125 |
| 3,800 | CG382T200X5L | 0.023 | 13.2 | 3.000 | 5.625 |
| 250 WVdc (300 Vdc Surge) | | | | | |
| 140 | CG141T250R2C | 0.310 | 1.5 | 1.375 | 2.125 |
| 375 | CG3750T250R4C | 0.130 | 3.1 | 1.375 | 4.125 |
| 600 | CG601T250V3C | 0.091 | 4.1 | 2.000 | 3.125 |
| 800 | CG801T250V4C | 0.072 | 4.6 | 2.000 | 4.125 |
| 3,000 | CG302T250X5L | 0.020 | 14.2 | 3.000 | 5.625 |
| 300 WVdc (350 Vdc Surge) | | | | | |
| 525 | CG5250T300V3C | 0.095 | 4.0 | 2.000 | 3.125 |
| 350 WVdc (400 Vdc Surge) | | | | | |
| 100 | CG101T350R2C | 0.720 | 1.0 | 1.375 | 2.125 |
| 180 | CG181T350R3C | 0.500 | 1.4 | 1.375 | 3.125 |
| 250 | CG251T350R4C | 0.290 | 2.1 | 1.375 | 4.125 |
| 400 | CG401T350V3C | 0.260 | 2.4 | 2.000 | 3.125 |
| 550 | CG551T350V4C | 0.180 | 3.3 | 2.000 | 4.125 |
| 2,000 | CG202T350X5L | 0.061 | 8.1 | 3.000 | 5.625 |
| 400 WVdc (475 Vdc Surge) | | | | | |
| 325 | CG3250T400V4C | 0.220 | 3.0 | 2.000 | 4.125 |
| 450 WVdc (525 Vdc Surge) | | | | | |
| 110 | CG111T450R4C | 1.220 | 1.0 | 1.375 | 4.125 |
| 240 | CG241T450V4C | 0.330 | 2.4 | 2.000 | 4.125 |

Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cornell Dubilier:

[CG203U025V4C](#) [CG751T200V3C](#) [CG2451T200X4C](#) [CG133U025V3C](#) [CG223U050X4C](#) [CG251T350R4C](#)
[CG273U016V3C](#) [CG232U035R2C](#) [CG132U100U3C](#) [CG732U050W4C](#) [CG801U050R2C](#) [CG502U050U3C](#)
[CG562U150X3L](#) [CG153U050W4C](#) [CG792U075W4C](#) [CG403U016V4C](#) [CG432U035R3C](#) [CG632U025R3C](#)
[CG3250T400V4C](#) [CG952U050V4C](#) [CG952U035V3C](#) [CG252U016R2C](#) [CG922U025R4C](#) [CG152U050R2C](#)
[CG652U016R2C](#) [CG152U075R4C](#) [CG101T350R2C](#) [CG102T200V4C](#) [CG102U075R3C](#) [CG102U100R4C](#)
[CG103U025U3C](#) [CG103U050X4C](#) [CG1052U016V3C](#) [CG111T450R4C](#) [CG112U035R2C](#) [CG113U035U4C](#)
[CG113U035W4C](#) [CG113U075X4C](#) [CG123U016R3C](#) [CG1252U075X5L](#) [CG141T250R2C](#) [CG143U035V4C](#)
[CG152U025R2C](#) [CG152U050R3C](#) [CG152U075R3C](#) [CG1551U150V4C](#) [CG164U010X5L](#) [CG1651T200W4C](#)
[CG1652U050X5L](#) [CG172U100W4C](#) [CG181T200R2C](#) [CG181T350R3C](#) [CG183U016R4C](#) [CG202T350X5L](#)
[CG202U050R4C](#) [CG202U075U3C](#) [CG203U025X4C](#) [CG212U035R3C](#) [CG213U016U3C](#) [CG223U035W4C](#)
[CG2251U100V4C](#) [CG241T450V4C](#) [CG252U050U3C](#) [CG252U075V3C](#) [CG252U100V4C](#) [CG252U150W4C](#)
[CG262U075U3C](#) [CG2750U150R2C](#) [CG282U025R3C](#) [CG292U050R3C](#) [CG302T250X5L](#) [CG323U025W4C](#)
[CG332U025R2C](#) [CG332U050V3C](#) [CG332U075V3C](#) [CG333U035X4C](#) [CG333U050X5L](#) [CG3451U075V4C](#)
[CG362U100W4C](#) [CG362U150X4C](#) [CG3750T250R4C](#) [CG382T200X5L](#) [CG401T350V3C](#) [CG401U100R2C](#)
[CG402U100W4C](#) [CG432U050R4C](#) [CG451T200R4C](#) [CG452U025U3C](#) [CG452U050V4C](#) [CG483U025X4C](#)
[CG492U075V4C](#) [CG501U150R3C](#) [CG5250T300V3C](#) [CG551T200U3C](#) [CG551T350V4C](#) [CG601T250V3C](#)
[CG601U075R2C](#) [CG602U025V3C](#) [CG652U050V3C](#) [CG742U050U4C](#)