

# swissbit®

Product Fact Sheet

## Industrial CFast™ Card

**F-50 Series**  
SATA III - 6.0 Gbit/s, MLC

Commercial and Industrial  
Temperature Grade

Date: February 28, 2019  
Revision: 1.05



# Product Fact Sheet

## F-50 Series



### Product Summary

- **Capacities:** 8 GBytes, 16 GBytes, 32 GBytes, 64 GBytes, 128 GBytes, 256 GBytes
- **Form Factor:** CFast™ 2.0 (36.4 mm x 42.8 mm x 3.6 mm)
- **Compliance:** SATA Revision 3.1 – 6 Gbit/s (3 Gbit/s and 1.5 Gbit/s backward compatible)
- **Command Sets:** Supports ATA/ATAPI-8 and ACS-2
- **Performance:**
  - Read Performance: Sequential Read up to 500 MBytes/s, Random Read IOPS up to 53,500
  - Write Performance: Sequential Write up to 330 MBytes/s, Random Write IOPS up to 74,000
- **Operating Temperature Range<sup>†</sup>:**
  - Commercial: 0 °C to 70 °C
  - Industrial: -40 °C to 85 °C
- **Storage Temperature Range:** -40 °C to 85 °C
- **Operating Voltage:** 3.3 V ± 5%
- **Power (Max Capacity):** Read (Active): 1.2 W; Write (Active): 2.0 W; Idle: 248 mW; Slumber: 17 mW
- **Data Retention:** 10 Years @ Life Begin / 1 Year @ Life End
- **Endurance in TeraBytes Written (TBW) Max Capacity<sup>†</sup>:** Client > 150; Enterprise > 7
- **Shock/Vibration:** 500 g / 20 g
- **Hardware BCH Code ECC:** up to 66 bit correction per 1 KByte page
- **NAND Flash Technology:** Multi-Level Cell (MLC)
- **Mean Time Between Failure:** > 2,000,000 hours
- **Data Reliability:** < 1 non-recoverable error per 10<sup>16</sup> bits read

### Product Features

- Dynamic and Static Wear Leveling
- Subpage Mode Flash Translation Layer (FTL)
- Active Data Care Management: Read Refresh
- Lifetime Enhancements
  - Dynamic Bad Block Remapping
  - Write Amplification Reduction
- On-Board Power Fail Protection
- AHCI, TRIM, and NCQ Support
- ATA Security Feature Set Support
- DEVSLP Compatible
- In-Field Firmware Update
- Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)
- Controlled "Locked" BOM
- 30 µinch Gold-Plated Connector (on request)
- Conformal coating (on request)
- Swissbit Life Time Monitoring (SBLTM) Tool and SDK for SBLTM (on request)

### Why Swissbit?

Swissbit is focused on the design, development, manufacture, and support of leading edge memory and storage solutions for the worldwide OEM/ODM marketplace. As a global supplier, Swissbit recognizes and addresses the higher level of application requirements of today's industrial, Netcom, and automotive customers by providing best-in-class products and services, with uncompromised attention to driving overall value and quality.

\* Adequate airflow is required to ensure the drive temperature, as reported in the S.M.A.R.T. data, does not exceed the specified maximum operating temperature.

† According to JEDEC (JESD471), the time to write the full TBW is a minimum of 18 months. Higher average daily data volume reduces the specified TBW. The values listed are estimates and are subject to change without notice.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Swissbit:

[SFCA128GH1AD4TO-C-LT-236-STD](#) [SFCA128GH2AD4TO-C-LT-236-STD](#) [SFCA128GH2AD4TO-I-LT-236-STD](#)  
[SFCA256GH2AD4TO-C-HT-236-STD](#) [SFCA256GH2AD4TO-I-HT-236-STD](#) [SFCA008GH2AD1TO-I-GS-236-STD](#)  
[SFCA008GH2AD1TO-C-GS-236-STD](#) [SFCA016GH2AD2TO-C-GS-236-STD](#) [SFCA016GH2AD2TO-I-GS-236-STD](#)  
[SFCA032GH2AD4TO-C-GS-236-STD](#) [SFCA032GH2AD4TO-I-GS-236-STD](#) [SFCA064GH2AD4TO-C-GS-236-STD](#)  
[SFCA064GH2AD4TO-I-GS-236-STD](#) [SFCA064GH2AD4TO-I-GS-226-STD](#)