










THIS DRAWING IS A CONTROLLED DOCUMENT. FILE NO. 1583006

TOOL NUMBER 	WIRE SIZE mm ² [AWG] 	INSULATION DIAMETER mm [in.] 	INSULATION ADJUST 	STRIP LENGTH mm [in.] 	FLIP LOCATOR 	CRIMP HEIGHT mm [in.] 	CONTACT PART NUMBERS [△]		CONTACT DESCRIPTION	APPLICATION SPECIFICATION
							LOOSE PIECE 	STRIP FORM 		
91558-1 91558-3	0.50 [20] 0.85 [18]	1.80-2.80 [071-.110]	NO	3.8-4.8 [150-.189]	NO	1.05-1.22 [041-.048] 1.05-1.32 [041-.052]	175218-[] 175289-[]	175196-[] 175286-[]	DYNAMIC Series D-3(L) Contacts	114-5148
91559-1 91559-3	0.20 [24] 0.30 [22] 0.50 [20]	1.20-1.60 [047-.063] 1.70-2.60 [067-.102]	NO	3.8-4.8 [150-.189]	NO	0.90-1.08 [035-.043] 0.97-1.13 [038-.044] 0.97-1.24 [038-.049]	175217-[] 175288-[]	175195-[] 175285-[]	DYNAMIC Series D-3(M) Contacts	114-5148
91560-1 91560-3	1.23-1.42 [16] 1.94-2.20 [14]	2.20-2.80 [087-.110]	NO	4.3-5.3 [169-.209]	NO	1.34-1.52 [053-.060] 1.57-1.76 [062-.069]	917511-[] 917512-[]	917484-[] 917485-[]	DYNAMIC Series D-3(2L) Contacts	114-5148
91561-1 91561-3	1.23-1.42 [16] 1.94-2.20 [14]	3.10-3.30 [122-.130] 3.50-3.80 [138-.150]	NO	4.3-5.3 [169-.209]	NO	1.34-1.52 [053-.060] 1.57-1.76 [062-.069]	353718-[] 353717-[]	353716-[] 353715-[]	DYNAMIC Series D-3(3L) Contacts	114-5148
91565-1 91565-3	0.08 [28] 0.12 [26]	0.80-1.20 [031-.047]	NO	3.8-4.8 [150-.189]	NO	0.67-0.96 [026-.038] 0.67-0.98 [026-.039]	175216-[] 175287-[]	175194-[] 175284-[]	DYNAMIC Series D-3(S) Contacts	114-5148
91576-1 91576-3	0.09-0.12 [28-26] 0.2 [24]	0.88-1.30 [035-.051] 1.11-1.43 [044-.056]	YES	2.9-3.9 [114-.154]	YES	0.58-0.7 [023-.028] 0.64-0.77 [025-.030]	1318108-[] 1318112-[]	1318106-[] 1318110-[]	DYNAMIC Series D-2(S) Contacts	114-5258
91595-1 91595-3	0.3-0.5 [22-20] 0.85 [18]	1.26-1.80 [050-.071] 1.79-1.90 [070-.075]	YES	2.9-3.9 [114-.154]	NO	0.87-1.03 [034-.041] 1.06-1.24 [042-.049]	1318107-[] 1318111-[]	1318105-[] 1318109-[]	DYNAMIC Series D-2(M) Contacts	114-5258
91596-1 91596-3	0.50 - 1.15 [20-18] 1.15-1.42 [16]	1.80-2.83 [071-.111] 2.35-3.23 [093-.127]	NO	4.3-4.8 [169-.189]	NO	1.35-1.50 [053-.059] 1.55-1.70 [061-.067]	1318986-6	1318985-6	DYNAMIC Series D-5(SS) Contacts	114-5206

[△] LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.


^③ -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY.
-3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.

[△] THIS TOOL USED FOR DUAL CRIMP APPLICATION.

5. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

2. AMP, CERTI-CRIMP, and DYNAMIC are trademarks.

CERTI-CRIMP II DATA SHEET

DWN: M. YOUNGER 21FEB2012		MATERIAL: -	HEAT TREAT: -
CHK: B.A. WOLFE 22FEB2012		 TE Connectivity	
APVD: B.A. WOLFE 22FEB2012			
NAME: B.A. WOLFE			
Certi-Crimp Tool Data Sheet Dynamic Series Connectors			
SCALE: -	SIZE: A1	DRAWING NO: 1583006	SHEET: 1 of 2 REV: A7

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TCI AND APPLICABLE TO THE COMPANY AND ITS PRODUCTS. IT IS TO BE USED ONLY BY THE PERSONNEL AUTHORIZED BY TCI. ANY UNAUTHORIZED DISCLOSURE OR USE OF THIS INFORMATION IS STRICTLY PROHIBITED. © 2018 TCI. ALL RIGHTS RESERVED.

THIS DRAWING IS A CONTROLLED DOCUMENT.

TOOL NUMBER 	WIRE SIZE mm ² [AWG] 	INSULATION DIAMETER mm [in.] 	INSULATION ADJUST 	STRIP LENGTH mm [in.] 	FLIP LOCATOR 	CRIMP HEIGHT mm [in.] 	CONTACT PART NUMBERS ¹		CONTACT DESCRIPTION	APPLICATION SPECIFICATION
							LOOSE PIECE 	STRIP FORM 		
2119141-1 2119141-3	0.09-0.12 [28-26] 0.20-0.38 [24-22]	1.08-1.50 [.042-.059]	NO	1.7-2.3 [.067-.091]	YES	0.59-0.69 [.023-.027] 0.69-0.79 [.27-.031]	1827587-2 1871743-1 1903116-2 1903124-1	-	DYNAMIC Series D 1000 M TYPE CONTACTS	114-5377
2119142-1 2119142-3	0.37-0.53 [22-20] 0.87 [18]	1.40 [.056] 2.20 [.087]	NO	1.7-2.3 [.067-.091]	YES	0.80-0.90 [.031-.035] 1.10-1.20 [.043-.047]	1827589-2 1871745-1 1903118-2 1903126-1	-	DYNAMIC Series D 1000 2L TYPE CONTACTS	114-5377
2119143-1 2119143-3	0.09-0.12 [28-26] 0.20-0.38 [24-22]	1.20-1.90 [.047-.075]	NO	1.7-2.3 [.067-.091]	YES	0.59-0.69 [.023-.027] 0.69-0.79 [.027-.031]	1827588-2 1871744-1 1903117-2 1903125-1	-	DYNAMIC Series D 1000 L TYPE CONTACTS	114-5377
2119144-1 2119144-3	0.05 [30] 0.09 [28]	0.60-1.30 [.024-.051]	NO	1.7-2.3 [.067-.091]	YES	0.49-0.59 [.019-.023] 0.52-0.62 [.020-.024]	1827586-2 1903115-2	-	DYNAMIC Series D 1000 S TYPE CONTACTS	114-5377
2119821-1 2119821-3 ⁴	DUAL WIRE APPLICATION 0.8 [18]	-	NO	2.85-3.15 [.112-.124]	YES	1.04-1.10 [.041-.043]	-	293389-1 293390-1	DYNAMIC Series D 1000 M TYPE CONTACTS (DUAL WIRE APPLICATION)	114-21150
2844985-1	0.50-1.15 [20-18] 1.15-1.42 [16]	1.80-2.70 [.071-.110] 2.40-3.23 [.094-.127]	YES	4.9-5.4 [.192-.213]	NO	1.19-1.29 [.047-.051] 1.35-1.45 [.053-.057]	2040015-2 2040016-1 1-2040016-2	2040587-1 2040586-1 1-2040586-1	DYNAMIC Series D 4000 S TYPE CONTACTS	114-5369
2305681-1	0.09-0.12 [28-26] 0.20-0.38 [24-22]	1.08-1.50 [.042-.059]	NO	1.7-2.3 [.067-.091]	YES	0.59-0.69 [.023-.027] 0.69-0.79 [.27-.031]	2316671-2 2316669-2	-	HD1 M TYPE CONTACTS	114-78021
2305682-1	0.37-0.53 [22-20] 0.87 [18]	1.40 [.056] 2.20 [.087]	NO	1.7-2.3 [.067-.091]	YES	0.80-0.90 [.031-.035] 1.10-1.20 [.043-.047]	2316671-4 2316669-4	-	HD1 2L TYPE CONTACTS	114-78021
2305683-1	0.09-0.12 [28-26] 0.20-0.38 [24-22]	1.20-1.90 [.047-.075]	NO	1.7-2.3 [.067-.091]	YES	0.59-0.69 [.023-.027] 0.69-0.79 [.027-.031]	2316671-3 2316669-3	-	HD1 L TYPE CONTACTS	114-78021
2305684-1	0.05 [30] 0.09 [28]	0.60-1.30 [.024-.051]	NO	1.7-2.3 [.067-.091]	YES	0.49-0.59 [.019-.023] 0.52-0.62 [.020-.024]	2316671-1 2316669-1	-	HD1 S TYPE CONTACTS	114-78021

¹ LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.

³ -1 IS A CERTICRIMP II HAND TOOL ASSEMBLY. -3 IS A CERTICRIMP II HEAD SUB-ASSEMBLY.

⁴ THIS TOOL USED FOR DUAL CRIMP APPLICATION.

5. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

2. AMP, CERTI-CRIMP, and DYNAMIC are trademarks.

CERTI-CRIMP II DATA SHEET

DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ±		DWN: M. YOUNGER 21FEB2012 DWR: B.A. WOLFE 22FEB2012 APVD: B.A. WOLFE 22FEB2012 NAME: B.A. WOLFE		MATERIAL: - HEAT TREAT: -	
ANGLE: - SURFACE TEXTURE: <input checked="" type="checkbox"/>		SCALE: - SIZE: A1 DRAWING NO: 1583006		SHEET: 2 of 2 REV: A7		CERTI-CRIMP TOOL DATA SHEET DYNAMIC SERIES CONNECTORS	
P LTR: - REVISION RECORD: - DATE: - DWN: - APVD: -		SEE SHEET 1		DATE: - DWN: - APVD: -		MATERIAL: - HEAT TREAT: -	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[91596-1](#)