

## Specification Sheet

Part Number: 148-00092



Clamp provides low insertion and high extraction force.  
Various sizes available to accommodate all different sizes of bundles.  
Clamp can be installed both before and after installation of bundles.

Wire Clamping Cable Ties, Version A, Diameter Attachment .17", 6.0" Long, Black, PA66HS, 500/pkg

**Article Number** 148-00092

**Type** T50SOSWA4.3E

**Color** Black (BK)

**Quantity Per** bag

**Product Description** Wire Clamping Cable Ties secure easily to wire frames for a tight fit and are available in four different wire frame sizes and two separate orientations to provide both perpendicular and parallel routing. The wire clamp design is ideally suited for easing the application process on the production floor by allowing for an easy snap fit of the harness assembly to the wire frame.

**Short Description** Wire Clamping Cable Ties, Version A, Diameter Attachment .17", 6.0" Long, Black, PA66HS, 500/pkg

**Global Part Name** T50SOSWA4.3E-PA66HS-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225

**Length L (Imperial)** 6.0

**Length L (Metric)** 150.0

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Width W (Imperial)** 0.18

**Width W (Metric)** 4.6

**Bundle Diameter Min (Imperial)** 0.06

**Bundle Diameter Min (Metric)** 1.6

**Bundle Diameter Max (Imperial)** 1.4

**Bundle Diameter Max (Metric)** 35.0

**Thickness T (Imperial)** 0.05

**Thickness T (Metric)** 1.3

<b>Diameter D (Imperial)</b>	0.17
<b>Nominal Diameter (Imperial)</b>	0.19
<b>Nominal Diameter (Metric)</b>	4.3
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988