

Installation contactors

ESB25N, EN25N



ABB's ESB..N Installation contactors are premium electromechanical switching devices widely used for controlling lighting, heating, ventilation, motors and pumps. The range covers ratings up to 100 A, includes various accessories and is fully compatible with other modular DIN-rail components.

ESB25N/EN25N installation contactors are used to control single-phase loads up to 25 A in household and industrial applications with a maximum ambient temperature of +55°C. Thanks to a new coil technology, they can be operated by AC or DC voltages, are completely hum-free and has an integrate overvoltage protection for the control circuit. A bi-colored indicator on the front of the device shows clearly the status of the contactor. Several contact combinations are available as well as tool-free mountable accessories. Versions with combined automatic and manual control are also part of the offer.

Product conformity & compliance

REACH (Regulation EC 1907/2006)

ESB25N/EN25N and related accessories were classified as articles and, during normal and reasonably foreseeable conditions of use, do not intentionally release any substance or preparation. ABB continuously undertakes communications throughout its supply chain in order to collect information about suppliers' compliance with REACH regulation.

SVHC (Regulation EC 1907/2006 REACH)

ABB continuously assesses its products for content of Substances of Very High Concern (SVHC), as included in the "Candidate List" by the European Chemicals Agency (ECHA). According to our best knowledge, ESB25N/EN25N and related accessories do not contain SVHC substances exceeding 0.1 % w/w.

RoHS II

ESB25N/EN25N and related accessories are within the scope of Directive 2011/65/EU (RoHS II) and Amendment 2015/863, starting from July 22 2019.

WEEE

The Waste Electrical and Electronic Equipment Directive (WEEE Directive) is the European Community directive 2012/19/EU on waste electrical and electronic equipment (WEEE) which, together with the RoHS directive, became European law in February 2003.

Product safety

Compliance with essential health and safety requirements has been assured by compliance with the applicable product and safety standards.

The validation according to the Product and Safety Standards is carried out by third party tests laboratory (STIEE / TL030) in respect of the EN ISO/IEC 17025 European standard, according to IECEE CB scheme. CB certificate has been issued.

Standards:

- IEC/EN 60947-1
- IEC/EN 60947-4-1
- IEC/EN 61095

- UL 60947-1

- UL 60947-4-1

Directives:


- EC "Low Voltage Directive" (LVD) 2014/35/EU

Material declaration

This section outlines the material composition of ESB25-40N-06 as representative products for the ESB25N/EN25N.

The constituent materials are distributed as follows.

The total weight of ESB25-40N-06 is 235 gr.




Material	% wt
1 PA	33.7 %
2 Other thermoplastic	0.4 %
3 Steel	40.3 %
4 Copper	17.9 %
5 Copper alloys	5.9 %
6 Stainless steel	0.1 %
7 Silver alloys	1.1 %
8 Electronic components	0.5 %
TOTAL	100 %

Packaging

The tables below provide information for each packaging material used. The card box used for the product material are made of recycled fibers and are 100 % recyclables.

ESB25-40N packaging material composition: total weight 20 gr.



Material	% wt
1 Cardbox	97.3 %
2 Paper	2.7 %
TOTAL	100 %

Product use



Energy

Power losses for installation contactor ESB25N/EN25N are indicated in the following table

Type		Power loss (W/device)
ESB25N	le / AC-1, AC-7a	11.2
	le / AC-3, AC-7b	4.0
	le / AC-3e	4.0
EN25N	le / AC-1, AC-7a	11.2
	le / AC-3, AC-7b	4.0
	le / AC-3e	4.0

End-of-life

At the end of operating life, constituent components of ESB25N/EN25N installation contactors have been optimized in order to reduce waste amount and increase recovery of the material. Metals and polymers contained into ESB25N/EN25N installation contactors are characterized by high recycling rates. Most plastic parts are marked for easy sorting.

ABB STOTZ-KONTAKT GmbH
Eppelheimer Strasse 82
69123 Heidelberg, Germany

abb.com/lowvoltage

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB AG does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB AG.
Copyright © 2020 ABB
All rights reserved