
KEMET Part Number: PFR5222J63J11L4BULK

(F411JH222J063C)



PFR/F411, Film, Film/Foil Polypropylene, General Purpose, 2200 pF, 5%, 63 VDC, 85°C, Lead Spacing = 5mm



General information			
Supplier:	KEMET		
Series:	PFR/F411		
Dielectric:	Film/Foil Polypropylene		
Style:	Radial		
Features:	Pulse		
RoHS: Yes			
Lead:	Wire Leads		
Miscellaneous:	An Operating Temperature Up To +105C Is Allowed Under Certain Conditions. Please Consult KEMET For Details.		

General Information

Dimensions			
L	7.2mm MAX		
Н	6mm MAX		
Т	4.5mm MAX		
S	5mm -0.4mm		
LL	4mm +1mm		
F	0.5mm +/-0.05mm		
G	0.5mm NOM		

1000

Packaging Quantity:

Н	6mm MAX		Capacitance:	2200 pF
Т	4.5mm MAX		Capacitance Tolerance:	5%
S	5mm -0.4mm		Voltage AC:	40 VAC
LL	4mm +1mm		Voltage DC:	63 VDC
F	0.5mm +/-0.05mm		Temperature Range:	-55/+100°C
G	0.5mm NOM		Rated Temperature:	85°C
			Dissipation Factor:	0.04% 1kHz, 0.05% 10kHz, 0.07% 100kHz
Packaging Specifications]	Insulation Resistance:	100 GOhms
			Max dV/dt:	1000 V/us
Packagin	g: Bulk, Bag		Inductance:	6 nH

Capacitance:	2200 pF	
Capacitance Tolerance:	5%	
Voltage AC:	40 VAC	
Voltage DC:	63 VDC	
Temperature Range:	-55/+100°C	
Rated Temperature:	85°C	
Dissipation Factor:	0.04% 1kHz, 0.05% 10kHz, 0.07% 100kHz	
Insulation Resistance:	100 GOhms	
Max dV/dt:	1000 V/us	
Inductance:	6 nH	

Specifications

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

