Data Sheet



Coaxial Panel Connector 13_BMA-50-0-2/199_N

Description

Straight panel receptacle plug, flange mount

Interface standards IEC 60169-33_MIL-STD-348A/321



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 18 \ \text{GHz} \end{array}$

Mechanical Data

Number of matings 1000 Weight 0.0025 kg

Environmental Data

Operating temperature -65 °C to 125 °C 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	
Gasket	NR (Natural Rubber)	

Related Documents

Catalogue drawing DCA-00011086

Ordering Information

Single package 13_BMA-50-0-2/199_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.