

PILOT

HIGH STANDARD PROTECTION

Its co-injected, ventilated frame guarantees unequalled adaptability and comfort.

 PLATINUM



PILOPSI





89 g

- + EXCELLENT FIELD OF VISION**
- + VERY FLEXIBLE PP/TPR FRAME**
- + ADJUSTABLE STRAP**
- + FITS OVER PRESCRIPTION GLASSES**
- + ANTI-SCRATCH & ANTI-FOG COATING**

bolle
SAFETY

PILOT

HIGH STANDARD PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
PILOT	Ventilated	PILOPSI	2C-1.2  1 BT KN C€	 EN166 3 4 BT C€	Anti-scratch/anti-fog ()

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

C€ European standard  Manufacturer name

FRAME MARKING


EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.

4. Large dust particles > 5 microns.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

PLATINUM

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CONDITIONNEMENT ET GENCOD EAN13	
	PILOPSI
Individual plastic bag	3660740003524
5 safety goggles per inner box	3660740103521
65 safety goggles per outer pack	3660740203528

CHARACTERISTICS	
LENSES	PC - 2,1 mm - Curve 5,5
FRAME	PP + TPR
TEMPLES	Non applicable
STRAP	Nylon
FOAM	No
SPARE LENSES	No



02/10/2015

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY