

This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0760155103</u>			. 1	
Status:	Active				
Overview:					
Description:		Header Module, 1.85mm by 3.70mm Pitch, Right Guide, Left Oper	n / 🔿	and shirts in	
		s, 140 Circuits, Mating Pin Length 4.70mm, Lead-Free			
				AN A	
Documents:			1 all	With the second s	
3D Model		Packaging Specification PK-70873-802-001 (PDF)		1	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		~~~~	
j v v	<u>n PS-75710-999-001 (P</u>				
		<u></u>	Series ima	ge - Reference only	
Agency Certification	on			· · ·	
UĽ		E29179	EU ELV		
			Not Relevant		
General					
Product Family		Backplane Connectors	EU RoHS	<u>China RoHS</u>	
Series		<u>76015</u>	Compliant		
Application		Backplane, Midplane, Orthogonal	REACH SVHC		
Component Type		PCB Header	Not Contained Per	Not Contained Per -	
Overview		GbX I-Trac Backplane Connector System	D(2021)4569-DC (8	
Product Name		GbX I-Trac	July 2021)		
UPC		800756834481	Halogen-Free		
			Status		
Physical			Low-Halogen		
Circuits (Loaded)		140		on, please visit <u>Contact US</u>	
Circuits (maximum)		140		en, please vielt <u>sentaet se</u>	
Color - Resin		Black	China ROHS	Green Image	
Durability (mating cycles max)		200	ELV	Not Relevant	
First Mate / Last Break		No	RoHS Phthalates	Not Contained	
Flammability		94V-0			
Guide to Mating Part		Yes			
Keying to Mating Part		None			
Material - Metal		High Performance Alloy (HPA)		Search Parts in this Series	
Material - Plating Mating		Gold	76015 Series		
Material - Plating Termination		Tin			
Material - Resin		High Temperature Thermoplastic	Mates With		
Net Weight		8.123/g	76020 GbX I-Tra	ac Right Angle Receptacle	
Number of Columns		10	Module		
Number of Pairs		4, Open Pin Field			
Number of Rows		7	Use With		
Orientation		Vertical		78227 GbX I-Trac Vertical Power	
PC Tail Length		2.10mm		Receptacle. <u>75234</u> Backplane Free Standir	
PCB Locator		No	Guide Pin		
PCB Retention		None			
PCB Thickness - Re	commended	1.60mm			
Packaging Type		Tray			
Pitch - Mating Interface		•	1.85mm, 3.70mm		
Pitch - Termination Interface			1.00mm, 2.70mm		
Plating min - Mating			0.762µm		
Plating min - Termination		•	0.762µm		
Polarized to PCB		•	Νο		
Stackable		No			
Stackable Surface Mount Compatible (SMC)		Yes			
Temperature Range - Operating		85°C			
Termination Interface: Style		Through Hole - Compliant Pin			
	e. Olyle				

Electrical

Current - Maximum per Contact Data Rate Shield Type Shielded Voltage - Maximum	1.0A 12.0 Gbps N/A No 120V AC (RMS)/DC			
Solder Process Data Lead-freeProcess Capability	N/A			
Material Info				
Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing	PK-70873-802-001 PS-75710-999-001 SD-76015-004-001			

This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION