

● Part Numbering

Safety Standard Certified Lead Type Disc Ceramic Capacitors for General Purpose

(Part Number)

DE	1	E3	RA	102	M	N4	A	N01	F
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩

① Product ID ② Series Category

Product ID	Code	Outline	Contents
DE	1	Safety Standard Certified	IEC60384-14 Class X1, Y1
	2		IEC60384-14 Class X1, Y2

For Electrical Appliance and Material Safety Law of Japan, the first three digits (① Product ID and ② Series Category) express "Series Name."

For Safety Certified Capacitors, the first three digits express product code. The fourth figure expresses certified type shown in ④ Safety Standard Certified Type column.

③ Temperature Characteristics

Code	Temperature Characteristics	Cap. Change or Temp. Coeff.	Temperature Range
B3	B	±10%	-25 to +85°C
E3	E	+20%, -55%	
F3	F	+30%, -80%	
1X	SL	+350 to -1000ppm/°C	+20 to +85°C

④ Rated Voltage/Safety Standard Certified Type

Code	⑨ Individual Specification Code	Rated Voltage	Safety Standard Certified Type
RA	N**	X1 : 440Vac (r.m.s.), Y1 : 250Vac (r.m.s.)	Type RA
	P**	X1 : 440Vac (r.m.s.), Y1 : 300Vac (r.m.s.)	
	Q**	X1 : 500Vac (r.m.s.), Y1 : 500Vac (r.m.s.), 1.5kVdc	
RB	R**	X1 : 760Vac (r.m.s.), Y1 : 500Vac (r.m.s.)	Type RB
KX	C**	X1 : 440Vac (r.m.s.), Y1 : 250Vac (r.m.s.)	Type KX
	N**	X1 : 440Vac (r.m.s.), Y1 : 250Vac (r.m.s.)	
	P**	X1 : 440Vac (r.m.s.), Y1 : 300Vac (r.m.s.)	
SA	T**	X1 : 300Vac (r.m.s.), Y2 : 250Vac (r.m.s.)	Type SA
	X**	X1 : 300Vac (r.m.s.), Y2 : 300Vac (r.m.s.)	
	Y**	X1 : 440Vac (r.m.s.), Y2 : 400Vac (r.m.s.), 1kVdc	
KY	M**	X1 : 250Vac (r.m.s.), Y2 : 250Vac (r.m.s.)	Type KY
	U**	X1 : 250Vac (r.m.s.), Y2 : 300Vac (r.m.s.)	

⑤ Capacitance

Expressed by three figures. The unit is pico-farad (pF). The first and second figures are significant digits, and the third figure expresses the number of zeros that follow the two numbers.

⑥ Capacitance Tolerance

Code	Capacitance Tolerance
J	±5%
K	±10%
M	±20%

⑦ Lead Style

Code	Lead Style	Dimensions (mm)		
		Lead Spacing	Lead Diameter	Pitch of Components
A2	Vertical Crimp Long	5	ø0.6±0.05	—
A3		7.5		
A4		10		
B2/J2	Vertical Crimp Short	5	ø0.6±0.05	—
B3/J3		7.5		
B4/J4		10		
N2	Vertical Crimp Taping	5	ø0.6±0.05	12.7
N3		7.5		15
N4		10		25.4

⑧ Packaging

Code	Packaging
A	Ammo Pack Taping
B	Bulk

⑨ Individual Specification Code

For part number that cannot be identified without "Individual Specification," it is added at the end of part number, expressed by three-digit alphanumerics.

⑩ Halogen-free Compatible Product