| | | TOP | VIEW | SIDE V | ΊEW | | | | | | |
|--------------------------|-----------|-------|-----------------------------|------------------------|-------------------------|---------------------------|--------------------|---------------------------|--------------------|--------------------|--|
| | | | Ø9±0.2 Ø12±0. | | 0.10±0.02 0.05±0.005 | 1 | | | | | |
| Specifications | | | Notes | | | Revision History | | | | | |
| Description | Value | Unit | | Notes | Version | | Description | | Date | Approved | |
| Resonant Frequency | 5,100 | (Hz) | 1) All dimensions are in mm | unless otherwise noted | 1 | Release | ed from Engi | neering | 10/21/2013 | J.S | |
| Resonant Impedance (Max) | 600 | (Ohm) | 2) All parts meet RoHS | | | | | | | | |
| Max Input Voltage | 30 | (V) |] | | | | | | | | |
| Capacitance | 12,000 | (pF) | | | | | | | | | |
| Plate Material | Alloy | | | | | | | | | | |
| Operating Temperature | -20 ~ +60 | °C | | | | | | | | | |
| Storage Temperature | -20 ~ +70 | °C | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | Drawn by | Date | Checked by | Date | Approved by | Date | |
| | | | | | Drawn by A.B. | Date 10/21/2013 | Checked by C.E. | Date 10/21/2013 | Approved by J.S | Date 10/21/2013 | |

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.