## JUNCTION BLOCKS POWER DISTRIBUTION ACCESSORIES





JBPT0 Series

JBPT2 and JBPT3 Series

#### **Description**

Junction Blocks are used as electrical connection points for the distribution of power or ground. These blocks can simplify cabling & architectures, and serve as convenient power tap points. Feed-thru versions enable firewall-mount applications and help reduce wiring costs and overall space required for cable routing. Junction blocks are available in various thread sizes and lengths. Lock washers and nuts are included with each block.

Pass-through junction blocks have high electrical ratings and low resistance due to a large cross-sectional contact area. Additionally, pass-through versions boast high installation torque values to allow the use of large cable sizes for high current applications. A plastic body locknut ensures quick and easy firewall-mount installation without the need for additional hardware.

#### **Ordering Information**

Ordering Information can be found on Page 2.

#### **Features and Benefits**

- Color-coordinated to serve as easy-to-identify power points
- Easy to install for quick distribution of power
- Impact-resistant plastic bodies

#### **Applications**

These products provide heavy-duty ground or power points of connections in your vehicle circuits. With both pass-through and surface mount options available, these products are flexible for application in any set-up requiring creating current routing.

#### **Web Resources**

Download 2D print, installation guide and technical resources at: **littelfuse.com/pdmaccessories** 

# JUNCTION BLOCKS POWER DISTRIBUTION ACCESSORIES

### **Ordering Information**

| PART NUMBERS    | DESCRIPTION   | MAXIMUM CURRENT   | OPERATING<br>TEMPERATURE<br>RANGE | STUD<br>MATERIAL          | THREAD<br>SIZE | MAXIMUM<br>MOUNTING<br>TORQUE (NM) | BODY<br>MATERIAL                      |
|-----------------|---|---|-----------------------------------|---------------------------|----------------|------------------------------------|---------------------------------------|
| JBPT0001Z       | Red Pass-Thru Junction<br>Block                             | 400Amps Max. (2/0 AWG, 125°C rated insulation or larger wire)     | -40°C TO 125°C                    | Stainless<br>steel        | 3/8 - 16       | 54.2                               | Nylon 66                              |
| JBPT0001Z-NC    | Red Pass-Thru Junction<br>Block (No Cap)                    | 400Amps Max. (2/0 AWG, 125°C rated insulation or larger wire)     | -40°C TO 125°C                    | Stainless<br>steel        | 3/8 - 16       | 54.2                               | Nylon 66                              |
| JBPT0002Z-NC    | Black Pass-Thru<br>Junction Block (No Cap)                  | 400Amps Max. (2/0 AWG, 125°C rated insulation or larger wire)     | -40°C TO 125°C                    | Brass                     | 3/8 - 16       | 54.2                               | Nylon 66                              |
| JBPT0003Z-NC    | Red Pass-Thru Junction<br>Block (No Cap)                    | 500Amps Max. (4/0 AWG, 125°C rated insulation or larger wire)     | -40°C TO 125°C                    | Stainless<br>steel        | 1/2 - 13       | 27                                 | Nylon 66                              |
| JBPT0004Z-NC    | Black Pass-Thru<br>Junction Block (No Cap)                  | 500Amps Max. (4/0 AWG, 125°C rated insulation or larger wire)     | -40°C TO 125°C                    | Stainless<br>steel        | 1/2 - 13       | 27                                 | Nylon 66                              |
| JBPT13802Z2B-NC | Black High Current Pass-<br>Thru Junction Block<br>(No Cap) | _   | _                                 | _                         | 3/8 - 16       | 54.2                               | Nylon 66                              |
| JBPT13802Z2R-NC | Red High Current Pass-<br>Thru Junction Block<br>(No Cap)   | _   | _                                 | _                         | 3/8 - 16       | 54.2                               | Nylon 66                              |
| JBPT2N02ZXB     | Black Surface Mount<br>Junction Block                       | 400A (Cable per SAE J378: 4/0<br>AWG, conductor insulation 125°C) | -40°C TO 125°C                    | Stud Steel<br>Zinc Plated | 1/2"-13        | 5                                  | Nylon PA66<br>(30% Glass,<br>UL94 V0) |
| JBPT2P01ZXR     | Red Pass-Thru Junction<br>Block                             | 400A (Cable per SAE J378: 4/0<br>AWG, conductor insulation 125°C) | -40°C TO 125°C                    | Stud Steel<br>Zinc Plated | 1/2"-13        | 5                                  | Nylon PA66<br>(30% Glass,<br>UL94 V0) |
| JBPT3N03ZXB     | Black Surface Mount<br>Junction Block                       | 250A (Cable per SAE J378: 0<br>AWG, conductor insulation 125°C)   | -40°C TO 125°C                    | Stud Steel<br>Zinc Plated | 3/8"-16        | 5                                  | Nylon PA66<br>(30% Glass,<br>UL94 V0) |
| JBPT3N04ZXB     | Black Surface Mount<br>Junction Block                       | 250A (Cable per SAE J378: 0<br>AWG, conductor insulation 125°C)   | -40°C TO 125°C                    | Stud Steel<br>Zinc Plated | M8X1.25        | 5                                  | Nylon PA66<br>(30% Glass,<br>UL94 V0) |
| JBPT3N04ZXR     | Red Surface Mount<br>Junction Block                         | 250A (Cable per SAE J378: 0<br>AWG, conductor insulation 125°C)   | -40°C TO 125°C                    | Stud Steel<br>Zinc Plated | M8X1.25        | 5                                  | Nylon PA66<br>(30% Glass,<br>UL94 V0) |
| JBPT3P01ZXB     | Black Pass-Thru<br>Junction Block                           | 250A (Cable per SAE J378: 0<br>AWG, conductor insulation 125°C)   | -40°C TO 125°C                    | Stud Steel<br>Zinc Plated | 3/8"-16        | 5                                  | Nylon PA66<br>(30% Glass,<br>UL94 V0) |
| JBPT3P02ZXB     | Black Pass-Thru<br>Junction Block                           | 250A (Cable per SAE J378: 0<br>AWG, conductor insulation 125°C)   | -40°C TO 125°C                    | Stud Steel<br>Zinc Plated | 3/8"-16        | 5                                  | Nylon PA66<br>(30% Glass,<br>UL94 V0) |



## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

#### Littelfuse:

JBPT2N02ZXB JBPT0001Z-NC JBPT3P01ZXB JBPT5N01ZXB JBPT0001Z JBPT3N03ZXB JBPT3P02ZXB 46211-R 46210-02 46211-01 46210-03 JBPT3N04ZXB 97846-A 97846-B