


KRPA Series Panel Plug-in Relay

- 5 to 10A current capability
- Contact arrangements of 1, 2 and 3 form C (CO)
- Octal type termination for quick installation
- Indicator lamp available on certain models



Typical applications
Baggage handling, lighting, inspection equipment, marine.

Approvals

UL E22575; CSA LR15734
Technical data of approved types on request.

Contact Data

Contact arrangement	1 form C (CO), 2 form C (CO), 3 form C (CO)	
Rated voltage	240VAC	
Rated current	10A	
Contact material	Ag	AgCdO
Min. recommended contact load	100mA, 12VDC	300mA, 12VDC
Frequency of operation	360 ops./hour	360 ops./hour

Contact ratings

Type	Load	Cycles
UL 508 KRPA, Ag	5A, 120VAC	100x10 ³
	3A, 240VAC	100x10 ³
	1/10HP, 120VAC	1x10 ³
	1/6HP, 240VAC	1x10 ³
	KRPA, AgCdO	
KRPA, AgCdO	10A, 240VAC	100x10 ³
	1/3HP, 120VAC	1x10 ³
	1/2HP, 240VAC	1x10 ³
KA, Ag	5A, 120VAC	
	3A, 240VAC	
	1/10HP, 120VAC	
	1/6HP, 240VAC	
KA, AgCdO	10A, 120VAC	
	6A, 240VAC	
	1/6HP, 120VAC	
	1/3HP, 240VAC	
Mechanical endurance		10x10 ⁶ ops.

Coil Data

Coil voltage range	6 to 220VDC 6 to 240VAC
Coil insulation system according UL	Class B

Coil versions, DC coil

Coil code	Rated voltage VDC	Operate voltage VDC	Coil resistance Ω±10%	Rated coil power W
6	6	4.5	32	1.15
12	12	9.0	120	1.2
24	24	18.0	472	1.25
48	48	36.0	1800	1.3
110	110	82.5	10000	1.2
-	220	Use 110V relay with 10KΩ, 5W resistor in series		

All figures are given for coil without preenergization, at ambient temperature +23°C.

Coil Data (continued)

Coil versions, AC coil

Coil code	Rated voltage VAC	Operate voltage VAC	Coil resistance Ω±15%	Rated coil power VA
6	6	5.1	6	2.01
12	12	10.2	24	2.02
24	24	20.4	85	2.02
120	120	102.0	2250	2.1
240	240	204.0	9110	2.1

All figures are given for coil without preenergization, at ambient temperature +23°C.

Insulation Data

Initial dielectric strength	
between open contacts	1000V _{rms}
between contact and coil	1000V _{rms}
between adjacent contacts	1000V _{rms}
Initial insulation resistance	
between insulated elements	KRPA: 1000MΩ KA: 100MΩ

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customer-support/rohssupportcenter

Ambient temperature	
DC coil	KRPA: -45°C to 70°C KA: -45°C to 85°C
AC coil	KRPA: -45°C to 55°C KA: -45°C to 70°C
Category of environmental protection	
IEC 61810	RT1 - dust protected KRPA and RTO - open style KA
Terminal type	KRPA: 8- or 11-pin octal-type plug KA: solder terminals
Weight	85g
Packaging/unit	tray/25 pcs., box/150pcs.

Accessories

For details see datasheet Sockets and Accessories, KRPA Relays

Product Code	Description
27E891	Two pole DIN socket (use 20C318 clip)
27E892	Three pole DIN socket (use 20C318 clip)
27E122	Two pole track mount socket (use 20C318 clip)
27E123	Three pole track mount socket (use 20C318 clip)

KRPA Series Panel Plug-in Relay (Continued)

Product Code	Arrangement	Contact Material	Coil	Option	Part Number			
KA-5AG-120	1 form C, 1 CO	AgCdO	120VAC	Open style	7-1393099-1			
KA-5AY-120		Ag			7-1393099-3			
KA-5DG-6		AgCdO			6VDC	7-1393099-9		
KA-5DG-12					12VDC	7-1393099-7		
KA-5DG-110	2 form C, 2 CO		110VDC		7-1393099-6			
KA-11AG-120			120VAC		3-1393099-6			
KA-11AY-6		Ag	6VAC		4-1393099-1			
KA-11AY-24			24VAC		4-1393099-0			
KA-11AY-120			120VAC		3-1393099-9			
KA-11DG-12		AgCdO	12VDC		4-1393099-3			
KA-11DG-24			24VDC		4-1393099-5			
KA-11DG-110			110VDC		4-1393099-2			
KA-14AG-120		3 form C, 3 CO		120VAC		5-1393099-0		
KA-14AY-120			Ag			5-1393099-4		
KA-14DG-24	AgCdO		24VDC		5-1393099-7			
KA-14DG-110			110VDC		5-1393099-5			
KRPA-5AG-24	1 form C, 1 CO			24VAC	None	9-1393104-9		
KRPA-5AG-120				120VAC		9-1393104-8		
KRPA-5DG-6			6VDC	1393105-5				
KRPA-5DG-12			12VDC	1393105-3				
KRPA-5DG-24			24VDC	1393105-4				
KRPA-5DY-12		Ag	12VDC			1393105-6		
KRPA-5DY-24			24VDC			1393105-7		
KRPA-11AG-6			2 form C, 2 CO	AgCdO		6VAC		2-1393104-8
KRPA-11AG-12						12VAC		2-1393104-4
KRPA-11AG-24				24VAC			1-1393105-2	
KRPA-11AG-120		120VAC			2-1393104-5			
KRPA-11AG-240		240VAC			2-1393104-7			
KRPA-11AN-12		12VAC		Indicator	3-1393104-1			
KRPA-11AN-24		24VAC			3-1393104-3			
KRPA-11AN-120		120VAC			3-1393104-2			
KRPA-11AN-240		240VAC			3-1393104-4			
KRPA-11AY-6	Ag	AgCdO		6VAC	None	3-1393104-9		
KRPA-11AY-12			12VAC	3-1393104-5				
KRPA-11AY-24			24VAC	3-1393104-7				
KRPA-11AY-120			120VAC	3-1393104-6				
KRPA-11AY-240			240VAC	3-1393104-8				
KRPA-11DG-6				6VDC			4-1393104-7	
KRPA-11DG-12				12VDC			4-1393104-3	
KRPA-11DG-24				24VDC			4-1393104-5	
KRPA-11DG-48				48VDC			4-1393104-6	
KRPA-11DG-110				110VDC			4-1393104-2	
KRPA-11DG-125		125VDC		4-1393104-4				
KRPA-11DG-24		24VDC		4-1393104-5				
KRPA-11DG-48		48VDC		4-1393104-6				
KRPA-11DN-12		12VDC	Indicator	5-1393104-0				
KRPA-11DN-24		24VDC		5-1393104-1				
KRPA-11DN-110		110VDC		4-1393104-9				
KRPA-11DY-12	Ag	AgCdO	12VDC	None	5-1393104-6			
KRPA-11DY-24			24VDC		5-1393104-7			
KRPA-14AG-12			3 form C, 3 CO		AgCdO	12VAC		6-1393104-4
KRPA-14AG-24		24VAC			6-1393104-7			
KRPA-14AG-120		120VAC			6-1393104-5			
KRPA-14AG-240		240VAC			6-1393104-8			
KRPA-14AN-24		24VAC		Indicator	7-1393104-4			
KRPA-14AN-120		120VAC			7-1393104-3			
KRPA-14AN-240		240VAC			7-1393104-5			
KRPA-14AY-24	Ag	AgCdO		24VAC	None	7-1393104-8		
KRPA-14AY-120				120VAC		7-1393104-7		
KRPA-14AY-240				240VAC		7-1393104-9		
KRPA-14DG-12	AgCdO	AgCdO	12VDC		8-1393104-2			
KRPA-14DG-24			24VDC		8-1393104-4			
KRPA-14DG-48			48VDC		8-1393104-5			
KRPA-14DG-110			110VDC		8-1393104-1			
KRPA-14DG-125			125VDC		8-1393104-3			
KRPA-14DN-24				24VDC	Indicator	9-1393104-0		
KRPA-14DY-24			Ag			None	9-1393104-3	