



### Main

Range	Easy TeSys
Device short name	GPEFC
Product or Component Type	Auxiliary contact block
Mounting Location	Front side
Pole contact composition	1 NO + 1 NC
Connections - terminals	Screw clamp terminals1 0.00...0.00 in <sup>2</sup> (1... 2.5 mm <sup>2</sup> ) - solid Screw clamp terminals2 0.00...0.00 in <sup>2</sup> (1... 2.5 mm <sup>2</sup> ) - solid Screw clamp terminals1 0.00...0.00 in <sup>2</sup> (0.75... 2.5 mm <sup>2</sup> ) - flexible without cable end Screw clamp terminals2 0.00...0.00 in <sup>2</sup> (0.75... 2.5 mm <sup>2</sup> ) - flexible without cable end Screw clamp terminals1 0.00...0.00 in <sup>2</sup> (0.75... 1.5 mm <sup>2</sup> ) - flexible with cable end
Quantity per Set	Set of 10

### Complementary

[Ui] rated insulation voltage	300 V UL 60947-4-1 300 V cUL 250 V IEC 60947-1
[Ue] rated operational voltage	24...240 V AC 24...60 V DC
[Ith] conventional free air thermal current	2.5 A
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA 110...120 V AC-15 100000 cycles 120 VA 230...240 V AC-15 100000 cycles 48 VA 24 V AC-15 100000 cycles 60 VA 48 V AC-15 100000 cycles
Rated operational power in W	15 W 48 V DC-13 100000 cycles 24 W 24 V DC-13 100000 cycles 9 W 60 V DC-13 100000 cycles
Tightening torque	12.39 lbf.in (1.4 N.m) screw clamp terminals
Height	0.43 in (11 mm)
Width	1.77 in (45 mm)
Depth	1.14 in (29 mm)
Net Weight	0.04 lb(US) (0.02 kg)

### Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

Category	22364-EASY TESYS GP2E1
Discount Schedule	I13
GTIN	3606481063496
Nbr. of units in pkg.	1
Package weight(Lbs)	0.71 oz (20.0 g)
Returnability	Yes
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.14 in (2.9 cm)
Package 1 width	1.77 in (4.5 cm)
Package 1 Length	0.43 in (1.1 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	220
Package 2 Weight	10.75 lb(US) (4.877 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[GPEFC11](#)