

CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Device connector front mounting, series: CA, straight, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 16+3, Direction of rotation: Standard, contact connection type: Pin, Solder connection, Flat gasket, 4x Ø 3.2, flange dimensions: 25 mm x 25 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243919

Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Solder connection: proven connection technology for various litz wires

Commercial data

Item number	1619956
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB31
Product key	ABRAEL
Catalog page	Page 101 (C-2-2019)
GTIN	4046356820264
Weight per piece (including packing)	32.2 g
Weight per piece (excluding packing)	28.45 g
Customs tariff number	85366990
Country of origin	DE

CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

Technical data

Product properties

Product type	Circular connectors (device side)
--------------	-----------------------------------

Connector

Insulating body

Coding	N
Insulation body material	PA 6.6
Contact material	CuZn
Contact surface material	Ni/Au
Insertion/withdrawal cycles	100
Connection method	Solder connection
Contact switching type	Pin
Application	Signal
Number of positions	19
Direction of rotation	Standard
Connection profile	16+3
Contact diameter Power contacts	1.5 mm
Litz wire cross-section Power contacts max.	1 mm ²
Rated current Power contacts	10 A
Rated voltage	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
Contact diameter Signal contacts	1 mm
Litz wire cross-section Signal contacts max.	1 mm ²
Nominal current per signal contact	8 A
Installation height	2000 m

Housing

Housing material	GD-Zn
Flange dimensions	25 mm x 25 mm
Type of locking	for standard and SPEEDCON interlock
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Environmental and real-life conditions

Ambient conditions

CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

Ambient temperature (operation)

-40 °C ... 125 °C

CA-19P1N122S00 - Device connector front mounting




1619956

<https://www.phoenixcontact.com/us/products/1619956>

Drawings

Schematic diagram



Connector pin assignment

CA-19P1N122S00 - Device connector front mounting





1619956

<https://www.phoenixcontact.com/us/products/1619956>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619956>

 cUL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Power	48 V	6 A	- 18	-
Signal	48 V	5 A	- 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Power	48 V	10 A	- 18	-
Signal	48 V	8 A	- 18	-

cULus Recognized				
-------------------------	--	--	--	--

CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

1619956

<https://www.phoenixcontact.com/us/products/1619956>

Accessories

SF-Z0019 - Protective cap

1607449

<https://www.phoenixcontact.com/us/products/1607449>



Plastic protection cap, with eye, IP40 for connectors with M23 external thread, RF, SF series

RC-Z2469 - Protective cap

1611797

<https://www.phoenixcontact.com/us/products/1611797>



Plastic protection cap, antistatic, for RF, SF, CA, RC series connectors, with M23 external thread

CA-19P1N122S00 - Device connector front mounting

1619956

<https://www.phoenixcontact.com/us/products/1619956>

RC-Z2104 - Metal protective cap

1604260

<https://www.phoenixcontact.com/us/products/1604260>



Metal protective cap, M23, degree of protection: IP67, series: RC, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241739

RC-Z2068 - Metal protective cap

1604236

<https://www.phoenixcontact.com/us/products/1604236>



Metal protective cap, M23, degree of protection: IP67, series: RC, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241735

CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

CA-Z0120 - Color coding

1620704

<https://www.phoenixcontact.com/us/products/1620704>

Color coding, color: green



CA-Z0121 - Color coding

1620705

<https://www.phoenixcontact.com/us/products/1620705>

Color coding, color: orange



CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

CA-Z0122 - Color coding

1620706

<https://www.phoenixcontact.com/us/products/1620706>

Color coding, color: black



CA-Z0001 - Contact removal tool

1620699

<https://www.phoenixcontact.com/us/products/1620699>

Unlocking tool for contact carriers for snapping in the M23 signal device connectors



CA-19P1N122S00 - Device connector front mounting



1619956

<https://www.phoenixcontact.com/us/products/1619956>

PROT-M23PRO-OT-IP20 - Plastic protective cap

1055753

<https://www.phoenixcontact.com/us/products/1055753>

Plastic protective cap, M23, degree of protection: IP20, series: M23 PRO



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com