



TECHNICAL DATA

'' D '' SUBMINIATURE CONNECTORS

SHELL: Steel .  
finish :tinned  
BODY: Glass filled thermoplastic.  
Flame retardant to UL 94 V-0 .  
Colour : black .

CONTACTS: Material for sockets : brass  
Material for pins : brass  
Finish of contact mating area :  
Gold over Ni

ELECTRICAL: Voltage proof >1000 V Rms to 50Hz .  
Nominal current 7,5 A (size20) 20 A (size8).  
Contact resistance <5m Ohms .  
Insulator resistance >5000 M Ohms .

CLIMATIC : Temperature range -55°C up to 85°C  
Damp heat 21 days ( + 40 - 95 % RH )  
Other climatic specifications in accordance  
with NF C 93-425, sheet HE501 and MIL C 24-308 .

MECHANICAL: Mating and unmating force size E 30 N max. 3.5 N mini.  
A 50 N max. 4.4 N mini.  
B 83 N max. 8.0 N mini.  
C 123 N max. 11.0 N mini.  
D 166 N max. 14.5 N mini.

L \*\*7D \* \*\* \* F179

L = RoHS

77D Shell steel tinned  
717D with Dimples plug only.

Shell size: E-A-B-C-D

Mounting type  
Without

Configuration:  
9- 15- 25- 37- 50

Contacts:  
Wire Wrap  
2 winding

Option:

Contact type : S - female  
                  : P - male

Boite boitier	A	B	B'	C	D	D'	E	F ±0,05	Pas	G	*
E	11,1	6,2	11,1	9,6	9,6	9,6	9,6	10,98	2,74	7,62	2x3
A	19,20	7,62	19,20	12,7	12,7	12,7	12,7	19,20	2,74	7,62	2x5
B	33,12	12,7	33,12	20,32	20,32	20,32	20,32	33,12	2,76	7,62	2x8
C	49,68	20,32	49,68	33,12	33,12	33,12	33,12	49,68	2,76	7,62	2x12
D	71,62	33,12	71,62	49,68	49,68	49,68	49,68	71,62	2,76	10,5	2x12

Amphenol Socapex  
Usine de Dole

IND.	MODIFICATIONS	EXEC.	DATE	Approb.	N°SERIE	017F	ECH.	ENS.	PLAN NOTICE	NOTICE-17D	IND.
------	---------------	-------	------	---------	---------	------	------	------	-------------	------------	------

DATE DU TRACÉ DESIGNATION L \*\* 7D \* \* \* \* F 179

COMMUNICATION ET UTILISATION INTERDITES SAUF AUTORISATION