



DH25CU Product Details

[Share](#) | [Print](#) | [Email](#)


✔ Active

Contactors

DH25CU=CONTACTOR

DH25CU (1616017-4)

TE Internal Number: 1616017-4

Product Highlights [View All](#)

- Contactor Type = Sealed
- DH-25 Series
- DC Actuating System
- 3 Poles
- Contact - Arrangement = 3PST-NO

[Pricing & Availability](#) >

[Request Sample](#) >

[Add to My Part List](#) +

[Buy Product through Distributor](#) >

Feedback

[Documents](#)

[Features](#)

[Compliance](#)

Please Note:

Use the Product Drawing for all design activity

Product Type Features	
Contactor Type	Sealed
Terminal Configuration	1/4-28-UNF-2A Stud
Mechanical Attachment	
Mounting Plate	With
Electrical Characteristics	
Actuating System [?]	DC
Contact Rating	120A
Coil - Rated Voltage (VDC) [?]	18 - 32 ▼
Coil Voltage, Max. (VDC) [?]	32
Frequency	400 Hz
Contact - Limiting Continuous Current-obs	Continuous
Termination Features	
Auxiliary Contact Terminals	6-32 UNC-2A
Coil Termination	6-32 UNC-2A Stud

Body Features	
Torque	56 In-lbs (Mains) 7.5 In-lbs (Coil, Aux)
Arc Cover	With
Mount Type	Chassis
Contact Features	
Number of Poles [?]	3
Configuration Features	
Contact - Arrangement [?]	3PST-NO ▼
Auxiliary Switch Contact Arrangement	2PST-1NO-1NC
Industry Standards	
RoHS/ELV Compliance [?]	Not ELV/RoHS compliant
Lead Free Solder Processes [?]	Not relevant for lead free process
Other	
Series	DH-25
Brand	Hartman

Related Products

Not quite the product you're looking for?

[Find Similar Products](#)

[View Part in Product Feature Selector](#)

[Check for Tooling](#)

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [Global Accessibility Statement](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

