# 1776293-4 ACTIVE

## Europa

TE Internal #: 1776293-4

Barrier Strips, Wire-to-Wire, 4 Position, 8 mm [.315 in] Centerline, 1 Row, Operating Voltage 250 V, 26 – 12 AWG Wire Size, .12 – 3.3

mm<sup>2</sup> Wire Size
View on TE.com >



Connectors > Terminal Blocks & Strips > Barrier Strips











Connector System: Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 8 mm [.315 in]

Number of Rows: 1

Operating Voltage: 250 V

## **Features**

#### **Product Type Features**

Troduct Type realures	
Block Style	None
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Levels	1
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Operating Voltage	250 V
Body Features	
Quick Connect Tab Plating Material	Tin
Primary Product Color	Natural

Right Angle

**Product Orientation** 



#### **Contact Features**

Contact Base Material	Brass
Contact Current Rating (Max)	30 A
Mechanical Attachment	
Screw Plating Material	Zinc Chromate
Screw Material	Steel

Mounting Options 2.8mm Diameter Mounting Holes

Connector Mounting Type Panel Mount

## **Housing Features**

Thread Size

Housing Material	Polyamide 6
Centerline (Pitch)	8 mm[.315 in]

M3

UL 94V-2

### **Dimensions**

Product Length	30 mm
Wire Size	$.12 - 3.3 \text{ mm}^2$

## **Usage Conditions**

Operating Temperature Range	-35 - 100 °C[-31 - 212 °F]
operating remperature names	

## Operation/Application

Circuit Application	Power	
Industry Standards		

# UL Flammability Rating

Packaging Features

Packaging Quantity	1
Packaging Method	Package

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)



Candidate List Declared Against: JUNE 2023 (235)

SVHC > Threshold:

Pb (1.8% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





# Customers Also Bought



















TE Part #ZPF000000000122612 502-8027-00

### **Documents**

## **Product Drawings**

TSB23004DS=EUROPA TERM BLK,8MM

English

### **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_1776293-4\_O1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_1776293-4\_O1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1776293-4\_O1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1776293-4\_O.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1776293-4\_O.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1776293-4\_O.2d\_dxf.zip

English

3D PDF

3D

Barrier Strips, Wire-to-Wire, 4 Position, 8 mm [.315 in] Centerline, 1 Row, Operating Voltage 250 V, 26 – 12 AWG Wire Size, .12 – 3.3 mm² Wire Size



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

## **BUCHANAN TERMINAL BLOCKS CATALOG - EUROPA TERMINAL BLOCKS**

English

## Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English