


SMD ONE PORT 310.00E MHz SAW RESONATOR

ASR310S2



RoHS
Compliant



5 x 3.5 x 1.5mm

STANDARD SPECIFICATIONS:

CHARACTERISTICS		UNIT	MIN.	TYP.	MAX.
Center Frequency Fo		MHz	309.925	310.000	310.075
Tolerance from Fo		KHz		±75	
Insertion Loss		dB	-	1.5	2.2
Quality Factor	Unloaded	-		15,333	
	50Ω loaded			2,000	
Temperature Stability	Turnover Temperature	°C	24	39	54
	Turnover Frequency	KHz		Fc	
	Freq. Temp. Coefficient	ppm/°C ²		0.037	
Frequency Aging		ppm/year		±10	
DC Insulation Resistance		MΩ	1.0		
RF Equivalent RLC Model	Motional Resistance R ₁	Ω		19	29
	Motional Inductance L ₁	μH		118.143	
	Motional Capacitance C ₁	fF		2.2333	
	Shunt Capacitance C ₀	pF	1.8	2.1	2.4
Operating temp.		°C	-40°C to +85°C		
Storage temp.		°C	-40°C to +85°C		
Max. Rating	DC voltage	V	±10		
RF Power Dissipation		dBm	10		


Electrostatic Sensitive Device. Handle with precaution.

MARKING:

- ASR310 ZYX
(Z for month from A to L;
Y for year, i.e. 4 for 2004,
X: Traceability code)

PIN NO.	CONNECTIONS
1	Input/Output
3	Output/Input
2 & 4	Case Ground


TEST CIRCUIT:



NOTES:

- 1) Frequency aging is specified at 65°C or less.
- 2) The center frequency Fc, is the frequency of minimum IL with the resonator in the specified test fixture in a 50Ω test system with VSWR <=1.2.
- 3) Unless otherwise specified, case temperature is 25°C ± 2°C.
- 4) The design model values are for reference only. The capacitance C0 is the measured static capacitance between either pin 1 and ground or pin 2 to ground.

OUTLINE DRAWING:



Dimensions: inch

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS
ISO9001:2008
CERTIFIED



30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ABRACON:](#)

[ASR310S2](#)