

Note: This datasheet may be out of date. Please download the latest datasheet of LQH32CN220K53# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=LQH32CN220K53%23

#### "#" indicates a package specification code.

Size Code 3225 (1210) in mm (in inch)


LQH32CN220K53#



< List of part numbers with package codes > LQH32CN220K53K LQH32CN220K53L









| Packaging | Specifications   | Standard<br>Packing<br>Quantity |
|-----------|------------------|---------------------------------|
| К         | 330Embossed Tape | 7500                            |
| L         | 180Embossed Tape | 2000                            |

| Mass (typ.) |        |  |
|-------------|--------|--|
| 1 piece     | 0.045g |  |



When rated current is applied to the products, selftemperature rise shall be limited to  $20^{\circ}$ C max and inductance will be within  $\pm 10\%$  of initial inductance

1 of 3

#### Attention

value.

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# LQH32CN220K53#

Note: This datasheet may be out of date. Please download the latest datasheet of LQH32CN220K53# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=LQH32CN220K53%23

#### "#" indicates a package specification code.



### Specifications

| L size   | 3.2±0.3mm   |
|--|-------------|
| W size   | 2.5±0.2mm   |
| T size   | 1.55±0.15mm |
| Size code inch (mm)  | 1210 (3225) |
| Inductance   | 22µH±10%    |
| Inductance Test Frequency  | 1MHz        |
| Rated current (Itemp)<br>(Based on Temperature rise)                     | 250mA       |
| Max. of DC resistance  | 0.923Ω      |
| Class of magnetic shield   | No Shield   |
| Self resonance frequency<br>(min.)                                       | 19MHz       |
| Operating Temperature<br>Range(Self-temperature rise<br>is not included) | -40℃ to 85℃ |
| DC Resistance Intermediate<br>Values                                     | 0.71Ω±30%   |
| Series   | LQH32CN_53  |

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. Please download the latest datasheet of LQH32CN220K53# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=LQH32CN220K53%23


### "#" indicates a package specification code.



## Characteristic Data

LQH32CN220K53#





Impedance - Current Characteristics

Impedance - Frequency Characteristics

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

