

Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Sealable :	Unsealed
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	✔ 0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	✔ Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03
Minimum Cable Diameter [mm] :	2.03

Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Temperature Range :	-40 to 125
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	✔ Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0
Voltage Drop :	Less than 6.0

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.

