



SECTION J-J

4805 (3/13)

_____ VIEW FROM COMPONENT SIDE DIMENSIONS: mm

2		1	
P LTR A INI	REVISIONS DESCRIPTION TIAL RELEASE	DATE DWN APVD 19MAR15 D.S F.Y	
	N		
AND SHIELD: COPPER ALLO THERMALPLASTIC,UL 94V-	0		
NAL AND GROUND CONTACTS AREA: MEETS THE PERFORM SPECIFICATION 108-6010	ANCE REQUIREME 3; BASED ON TE	LCORDIA	
-CORE, APPLICATIONS IN NT PIN AREA: 0.5 um MIN R BASE PLATING		NVIRONMENTS	D
ARKED WITH PART NUMBER	AND DATE CODE		
BASIC DIMENSIONS ESTABL A LUBRICATED WITH BELLC		MER	
D LUBRICANT. TECHNICAL -CORE, ISSUE 2, DECEMBE	REFERANCE:		
THRU HOLE DIAMETER AND PLICATION SPEC 114-1305		NESSES PLEASE -	
			С
\wedge			
<u>4</u> <u>- Y - <u>4</u></u>			
BSC 4			
			В
$\overline{\nabla}$			
		2170902-1	
A CONTROLLED DOCUMENT. DWN 18DEC14 DAVID SHEN		PART NUMBER	А
CHK 18DEC14 TOLERANCES UNLESS OTHERWISE SPECIFIED: APVD 18DEC14 FRANK YANG APVD 18DEC14	ASSEMBLY DRAW	TE Connectivity	
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	SIZE CAGE CODE DRAWING NO	ER, 4PAIRS 10COLUMNS RESTRICTED TO	
FINISH - Customer Drawing	A 1 - C-217090 scale		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 2170902-1