

Flexible RF cable

G_03233 Item: 22510135

Description

G: RF cables with PE dielectrics

75 Ohm, 1 GHz, 85°C, ø5 mm, PVC jacket



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Strand-07	0.49 mm
Dielectric	PE (Polyethylene)		2.95 mm
Outer conductor	Copper	Braid, 95%	3.6 mm
Jacket	PVC (Polyvinyl chloride)	RAL 9005 - bk	5 mm +/- 0.15

Print: HUBER+SUHNER G 03233 75 Ohm (production order number)

Electrical Data

Impedance	75 Ω +/- 3
Operating Frequency	1 GHz
Capacitance	67 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Screening effectiveness	≥ 39 dB (up to 1 GHz)
Operating voltage	≤ 2.5 kV _{rms} (at sea level)
Test voltage	5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		3.9 kg/100 m
Min. bending radius	static	25 mm 50 mm

Environmental Data

Temperature range	-25 °C ... +85 °C
Installation temperature	-20 °C... +60 °C
Halogen free	No
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U12 3 mm / 75 Ohm
-------------	-------------------

Flexible RF cable

G_03233 **Item: 22510135**

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.4925

b = 0.035

f_{max} = 1

P at 1GHz = 82

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (W) sea level 40° C ambient temperature
0,05	0,11	0,034	367
0,1	0,16	0,049	259
0,15	0,2	0,060	212
0,2	0,23	0,069	183
0,25	0,26	0,078	164
0,3	0,28	0,085	150
0,35	0,3	0,093	139
0,4	0,33	0,099	130
0,45	0,35	0,105	122
0,5	0,37	0,111	116
0,55	0,38	0,117	111
0,6	0,4	0,123	106
0,65	0,42	0,128	102
0,7	0,44	0,133	98
0,75	0,45	0,138	95
0,8	0,47	0,143	92
0,85	0,48	0,147	89
0,9	0,5	0,152	86
0,95	0,51	0,156	84
1,0	0,53	0,161	82