

#### **BALLAST CONNECTORS**









TE CONNECTIVITY (TE)

# 2P PLUG, MINIATURE WATERPROOF CONN, BLACK

SlimSeal | SlimSeal Solid State Lighting Connectors

2-2834074-2

TE Internal Number: 2-2834074-2

**EU RoHS Compliant EU ELV Compliant** 

**Connector System** Wire-to-Wire

**Product Type** Connector

Contact Current Rating (Max) (A) 5

Termination Method to Wire/Cable Crimp

Centerline (mm) 2.5



## **PRODUCT DRAWING**

English



.

I 3D PDF

### **DOCUMENTATION**

**Product Drawings** 

# **Plug Miniature Waterproof Connetor**

PDF

**English** 

**CAD Files** 

#### **3D PDF**

PDF

3D

#### **Customer View Model**

2D\_DXF.ZIP

English	
Customer View Model	
Customer View Model  3D_IGS.ZIP	
English	
Customer View Model	
3D_STP.ZIP	
English	
Catalog Pages/Data Sheets	
Miniature IP67 Sealed Wire-To-Wire Connector Flyer	
PDF	
English	
Product Specifications	
Product Specification	
Product Specificatin For Miniature Waterproof Connector	
PDF	
English	
Application Specification	
Application Specification For Miniature Waterproof Connector	
PDF	
English	
Instruction Sheets	
Instruction Sheet (non U.S.)	
Instruction Sheet For Miniature Waterproof Connector  PDF	
English	
Agency Approvals	
UL Report	
Miniature Water Proof Connector	
PDF	
English	
FEATURES	+
Please review product documents or contact us for the latest agency approval information.	
Please Note: Use the Product Drawing for all design activity.	
Product Type Features	
Connector System Wire-to-Wire	
Product Type Connector	

Sealed No

Configuration Features

Number of Positions 2 Number of Rows 1
Electrical Characteristics
Operating Voltage (Max) (VAC) 400
Contact Features
Contact Current Rating (Max) (A) 5
Termination Features
Termination Method to Wire/Cable Crimp Tool-less Wire Termination No
Housing Features
Centerline (mm) 2.5
Dimensions
Wire/Cable Size (AWG) 18 – 22
Usage Conditions
Operating Temperature Range (°C) -40 – 105  UV Exposure Rated No
Identification Marking
Circuit Identification Feature With
Industry Standards
Agency/Standard Number UL 1977 Agency/Standard UL
UL Flammability Rating UL 94V-0
Statement of Compliance
Statement of Compliance PDF