
Noise Suppression Products/EMI Suppression Filters > EMIFIL® (Capacitor type) > Single Circuit Type for Large Current


Data Sheet

# EMIFIL<sup>®</sup> (Capacitor type) Single Circuit Type for Large Current NFM21PC Series (0805 Size)

## Dimensions



# Equivalent Circuit



## ■ Rated Value (□: packaging code)

Part Number	Capacitance	Rated Current	Rated Voltage	Insulation Resistance (min.)	Operating Temperature Range
NFM21PC104R1E3	0.1µF ±20%	2A	25Vdc	1000M ohm	-55 to +125°C
NFM21PC224R1C3	0.22µF ±20%	2A	16Vdc	1000M ohm	-55 to +125°C
NFM21PC474R1C3	0.47µF ±20%	2A	16Vdc	1000M ohm	-55 to +125°C
NFM21PC105B1A3	1.0µF ±20%	4A	10Vdc	500M ohm	-40 to +85°C
NFM21PC105B1C3	1.0µF ±20%	4A	16Vdc	500M ohm	-40 to +85°C
NFM21PC225B0J3	2.2µF ±20%	4A	6.3Vdc	200M ohm	-40 to +85°C
NFM21PC475B1A3	4.7µF ±20%	6A	10Vdc	100M ohm	-40 to +85°C

Number of Circuit: 1


Continued on the following page.  $\square$ 

•This data sheet is applied for CHIP EMIFIL<sup>®</sup> used for General Electronics equipment for your design.

#### 

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.



Insertion Loss Characteristics (Main Items)

#### Packaging

Code	Packaging	Minimum Quantity	
D	180mm Paper Tape	4000	
В	Bulk(Bag)	500	



Data Sheet

#### Continued from the preceding page.

#### ■ ①Caution/Notice

#### 

Do not use products beyond the rated current and rated voltage as this may create excessive heat and deteriorate the insulation resistance.

#### Notice

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

2

This data sheet is applied for CHIP EMIFIL® used for General Electronics equipment for your design.

/Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.



# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: NFM21PC474R1C3B NFM21PC105B1C3B