


# Han E M Crimp Contact Ag 0.5 mm<sup>2</sup>/ 20 AWG



Part number	09 33 000 6121
Specification	Han E M Crimp Contact Ag 0.5 mm²/ 20 AWG
HARTING eCatalogue	https://b2b.harting.com/09330006121

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Contacts
Series	Han E <sup>®</sup>
Type of contact	Crimp contact

#### Version

Gender	Male
Contact identification	No groove
Manufacturing process	Turned contacts

#### Technical characteristics

Conductor cross-section	0.5 mm²
Conductor cross-section	AWG 20
Rated current	≤16 A
Contact resistance	≤1 mΩ
Stripping length	7.5 mm
Mating cycles	≥500

## Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption

Page 1 / 2 | Creation date 2024-02-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany

Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



# Material properties

China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

## Specifications and approvals

Charifications	IEC 60664-1
Specifications	IEC 61984

## Commercial data

Packaging size	100
Net weight	1.1 g
Country of origin	Switzerland
European customs tariff number	85366990
GTIN	5713140049802
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors