

Mounting set for securing the batteries - BATTERY MOUNTING KIT - 2320788

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Used for mounting batteries that cannot be mounted on DIN rails.

Product Description

Mounting set, consisting of 4 metal brackets and a fabric lashing strap for fixing the rechargeable battery modules on a mounting plate.

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 741088
GTIN	4046356741088

Technical data

Dimensions

Width	80 mm
Height	25 mm
Depth	18 mm
Horizontal pitch	4.4 Div.

Classifications

eCl@ss

eCl@ss 10.0.1	27059290
eCl@ss 4.0	27040700
eCl@ss 4.1	27040700
eCl@ss 5.0	27242200
eCl@ss 5.1	27242200
eCl@ss 6.0	27049000
eCl@ss 7.0	27049005
eCl@ss 8.0	27059290
eCl@ss 9.0	27059290

Mounting set for securing the batteries - BATTERY MOUNTING KIT - 2320788

Classifications

ETIM

ETIM 3.0	EC001039
ETIM 4.0	EC002625
ETIM 5.0	EC002625
ETIM 6.0	EC002839
ETIM 7.0	EC002839

UNSPSC

UNSPSC 6.01	30211502
UNSPSC 7.0901	39121004
UNSPSC 11	39121004
UNSPSC 12.01	39121004
UNSPSC 13.2	39121004
UNSPSC 18.0	26111710
UNSPSC 19.0	26111710
UNSPSC 20.0	26111710
UNSPSC 21.0	26111710

Approvals


Approvals

Approvals

DNV GL / BV / LR / ABS

Ex Approvals

Approval details

DNV GL		https://approvalfinder.dnvgl.com/	TAA0000265
Nominal voltage UN	500 V		
Nominal current IN	41 A		
mm ² /AWG/kcmil	6		

Mounting set for securing the batteries - BATTERY MOUNTING KIT - 2320788

Approvals

BV		http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials	41516/A0 BV
----	--	---	-------------

LR		http://www.lr.org/en	17/20032
----	--	---	----------

ABS		http://www.eagle.org/eagleExternalPortalWEB/	15-GD1438179-PDA
-----	--	---	------------------

Accessories

Accessories

Battery unit

Energy storage - UPS-BAT/VRLA-WTR/24DC/13AH - 2320416



Energy storage device, lead AGM, VRLA technology, 24 V DC, 13 Ah, tool-free battery replacement, automatic detection, and communication with QUINT UPS-IQ

Energy storage - UPS-BAT/VRLA-WTR/24DC/26AH - 2320429



Energy storage device, lead AGM, VRLA technology, 24 V DC, 26 Ah, tool-free battery replacement, automatic detection, and communication with QUINT UPS-IQ

Energy storage - UPS-BAT/VRLA/24DC/38AH - 2320335



Energy storage device, lead AGM, VRLA technology, 24 V DC, 38 Ah, automatic detection, and communication with QUINT UPS-IQ

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2320788](#)